



760207308 | CPPA-UDDM-M-2U-48
Discrete Distribution Module Panel, Angled – 2U

Product Classification

| | |
|-----------------------|---|
| Portfolio | CommScope® |
| Product Type | Copper patch panel |
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |

Dimensions

| | |
|-----------------------------------|----------------------|
| Depth | 210.82 mm 8.30 in |
| Diameter Over Dielectric, maximum | 1.168 mm 0.046 in |
| Diameter Over Dielectric, minimum | 0.762 mm 0.030 in |
| Height | 88.90 mm 3.50 in |
| Width | 482.60 mm 19.00 in |

Electrical Specifications

| | |
|---|--------------------------------|
| ANSI/TIA Category | 5e 6 6A |
| Current Rating | 1.5 A @ 20 °C 1.5 A @ 68 °F |
| Dielectric Withstand Voltage, RMS, conductive surface | 1500 Vac @ 60 Hz |
| Dielectric Withstand Voltage, RMS, contact-to-contact | 1000 Vac @ 60 Hz |
| Insulation Resistance, minimum | 500 MOhm |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Flammability Rating | UL 94 V-0 |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Relative Humidity | Up to 95%, non-condensing |
| Safety Standard | cUL UL |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |

General Specifications

| | |
|-----------------------|--------------------|
| Total Ports, quantity | 48 |
| Cable Type | U/UTP (unshielded) |
| Brand | CommScope® |
| Color | Black |
| Package Quantity | 1 |
| Rack Type | EIA 19 in |
| Rack Units | 2 |

Mechanical Specifications

| | |
|---------------|---|
| Material Type | High-impact, flame retardant, thermoplastic Powder-coated steel |
|---------------|---|

760207308 | CPPA-UDDM-M-2U-48

Wiring

T568A | T568B

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2011/65/EU | Compliant |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |

