

Detectors and Edges

Gate Operator Vehicle Detectors and Safety Sensors



2500-2346-LP



2500-2377



2500-2509



2520-441



2120-478-YS



2500-150



2500-2112



2500-2010

Vehicle Detectors— for use as an opening, reversing device, or shadow loop

Loop Detector – plug-In style (fits APeX Controller)

- 2500-2346 Plug-in style loop detector, dual output
- 2500-2346-LP Plug-in style loop detector, dual output, low (8 mA) power
- 2500-2509 Harness, adapts non plug-in detectors to APeX, 36"

Loop Detectors – box style

- 2510-190 Single detector wired in operator (2500-2375)
- 2510-191 Two detectors wired in operator (2500-2375 x 2)
- 2500-2375 EDI LMA-100LV single relay, 12-24 VAC or DC
- 2500-2376 EDI LMA-200LV dual relay, 12-24 VAC or DC
- 2500-2377 EDI LMA-1250LV dual relay with display, 12-24 VAC or DC
- 2500-2378 EDI LMA-1250LP dual transistor output, 12-24 VDC, low power
- 2500-2196 Harness only, prewired DC power
- 2500-2420 Harness only

Probe Detectors - burial style – for use as opening devices only

cannot be used as a reversing device!

- 2500-1928 Detector - probe - 24 VAC - 50' lead
- 2500-1929 Detector - probe - 24 VAC - 100' lead
- 2500-1883 Detector - probe - 24 VAC - 150' lead
- 2500-2132 Detector - probe - 24 VDC - 100' lead
- 2500-2133 Detector - probe - 24 VDC - 150' lead
- 2500-2508 Integrated probe/detector - 9-35 volts AC/DC - low power (1.5 mA) - 100' lead

Loops & Sealant

- 2510-222 Loop wire kit with two sealants (200' of wire)
- 2510-015 Loop wire kit with one sealant (200' of wire)
- 2500-1502 Loop preformed in PVC, 6'x12'
- 2510-195 Loop preformed in PVC, 6'x15'
- 1600-542 Loop sealant tube (black)
- 1600-818 Loop sealant tube (gray)

Time Delay Systems

- 2500-2006 7-Day timer AC/DC
- 2500-1349 365-Day timer-holiday programming, battery back-up

Photo Electric Controls – for use as a reversing or stopping device with beam spanning gate opening

- 2520-031 Photo eye with reflector and hood, 28' range, UL Listed
- 2500-150 Photo eye with reflector only, 28' range, UL Listed
- 2520-441 Photo eye thru-beam, swivel mount with hardware, 165' range, UL Listed
- 2510-306 Photo eye, thru-beam, 165' range, 24 volt, NEMA 4, UL Listed
- 190-110742 Photo eye, thru-beam, 32' range, UL Listed
- 2120-478-YS Mounting pedestal for photo eyes (set), yellow (-031, -158, -441, -306 only)
- 2120-478-BT Mounting pedestal for photo eyes (set), black

Electric Gate Edges – for use as a reversing or stopping device

- 2520-300 Edge, MG020, 3' with channel
- 2510-281 Edge, MG020, 4' with channel
- 2510-042 Edge, MG020, 5' with channel
- 2510-349 Edge, MG020, 6' with channel
- 2500-2112 Edge, MGR20, 4', 2" round
- 2500-2009 Edge, MGR20, 5', 2" round
- 2500-2010 Edge, MGS20, 5', 2" square
- 2520-134 Edge, MG020, 5' with channel and 15' coil cord with junction box
- 2510-220 1051 Gate edge transmitter, Multi-Code, with mounting kit
- 2510-372 MGT Gate edge transmitter, MegaCode, with mounting kit