

CISCO® SFP-GE-T COMPATIBLE 1000BASE-T COPPER SFP (MINI-GBIC) TRANSCEIVER MODULE



SFP-GE-T-LEG | [Quiktron](#)

FEATURES & BENEFITS

This SFP (mini-GBIC) transceiver module is designed for use with Cisco network equipment and is equivalent to Cisco part number SFP-GE-T. This transceiver is built to meet or exceed the specifications of the OEM and to comply with Multi-Source Agreement (MSA) standards. This product is 100% functionally tested, and compatibility is guaranteed. The transceiver is hot-swappable input/output device which allows a Gigabit Ethernet port to link with a copper network. OEM specific configuration data is loaded on to the EEPROM of the transceiver at the factory, allowing this transceiver to initialize and perform identically to an OEM transceiver. This transceiver may be mixed and deployed with other OEM or third party transceivers and will deliver seamless network performance. A list of compatible network equipment is available on the Specs tab of this page. Cisco and the Cisco logo are trademarks or registered trademarks of Cisco Systems, Inc. This product is not certified or endorsed by Cisco Systems



- Functionally identical to Cisco SFP-GE-T
 - RJ45 port designed for use with Category Copper cabling
 - Gigabit Ethernet communication
 - Supports up to 100 meters of cabling
- Cisco Transceiver Equivalent - SFP-GE-T
Equipment Compatibility

WS-SUP32-8GE-3B WS-SUP32-10GE-3B WS-X6724-SFP WS-X6748-SFP WS-4448-GB-SFP WS-C3750-24PS WS-C3750-24TS WS-C3750-48PS
WS-C3750-48TS WS-C3750G-12S WS-C3750G-24PS WS-C3750G-24TS WS-C3750G-48PS WS-C3750G-48TS WS-C3560-24PS WS-C3560-48PS
WS-C3560-24TS WS-C3560-48TS WS-C3560G-24PS WS-C3560G-24TS WS-C3560G-48PS WS-C3560G-48TS WS-C2970G-24TS WS-C2950ST-8
LRE WS-C2950ST-24 LRE WS-C2950ST-24 LRE997 WS-C2948G-GE-TX WS-C2940-8TF-S WS-CE500-24LC WS-CE500-24PC WS-CE500G-12TC

SPECIFICATIONS

GENERAL INFO

Color: Silver
Type: SFP Transceiver

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

CORD INFORMATION

Connector Type End One: SFP

Connector Type End Two: RJ-45