Product Specifications



FFXLCSC42

LazrSPEED® 550 LC to SC, Fiber Patch Cord, 1.6 mm Duplex, LSZH

Product Classification

Portfolio CommScope® Brand LazrSPEED®

Product Type Fiber patch cord, duplex

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Construction Materials

Fiber Type OM4, LazrSPEED® 550

Total Fibers, quantity

Dimensions

Cord Length, maximum 325 ft | 99 m

Cord Length, minimum 2 ft | 1 m

Diameter Over Jacket 1.60 mm | 0.06 in

Ordering Note For lengths greater than 999 ft (304 m), orders must be in meters | Minimum

length may vary based on cable configuration

Environmental Specifications

Environmental Space Low Smoke Zero Halogen (LSZH) Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F) Operating Temperature, pending approval -20 °C to +70 °C (-4 °F to +158 °F)

General Specifications

Color, connector A Beige
Color, connector B Beige

Construction Type Duplex patch cord

Interface, connector A LC
Interface, connector B SC
Interface Feature, connector A Standard
Interface Feature, connector B Standard

Mechanical Specifications

Cable Retention Strength, maximum 4.40 lb @ 90 $^{\circ}$ 11.24 lb @ 0 $^{\circ}$

Regulatory Compliance/Certifications

AgencyRoHS 2011/65/EU

Classification
Compliant

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system



Product Specifications



FFXLCSC42

Included Products

N-002-ZC-5K-F16 (Product Component—not orderable) — LazrSPEED® 1.6mm Low Smoke Zero Halogen Riser Zipcord Cable

CS-5K-TB (Product Component—not orderable) — LazrSPEED® 550 OM4 Bend-Insensitive Multimode Fiber
 460125198 (Product Component—not orderable) — Pre-Radiused LC Connector duplex for 1.6 mm Fiber, multimode
 460125750 (Product Component—not orderable) — LazrSPEED® Pre-Radiused SC Connector for 1.6 mm Fiber Cordage, Duplex, multimode