# C-AR-A-SQT7 Series

LED Shoebox-Style Floodlight Replaces 320W PSMH/400W MH



# THE TRADITIONAL STYLE YOU LOVE, PAIRED WITH THE ENERGY SAVINGS YOU DESIRE (UP TO 65%)



Shown with 2" slip fitter (sold separately)

### PRODUCT SPECIFICATIONS

#### **OVERVIEW**

· Initial Delivered Lumens: 16,900

• CRI: ≥ 70

· CCT: Cool White 5000K, Neutral White 4000K

· Mounting: Sold Separately • Input Power: 119 Watts

· Dimmable: No

• Operating Minimum: -40°C (-40°F)

· Lifespan: Estimated >127,000 Hours

Power Factor: > 0.9

• Total Harmonic Distortion: < 20%

· Limited Warranty: 5 Years\*

· Replaces 320W PSMH/400W MH

EFFICIENT	FLEXIBLE	RECOMMENDED USE	INPUT VOLTAGE
<ul> <li>Over 75% energy savings compared to HID</li> <li>LED technology for reduced maintenance cycles</li> </ul>	<ul> <li>Mount in 0° - 180° orientations</li> <li>NEMA 7 beam angle for 110° flood (wide) distribution</li> </ul>	<ul><li> General Area Lighting</li><li> Parking Lots</li><li> Perimeter Lighting for Storage Areas</li></ul>	• Universal (120V through 277V Operation)

### **ORDERING INFORMATION**

Example: C-AR-A-SQT7-17L-50K-DB

C-AR-A	SQT7	17L		DB
PRODUCT	ТҮРЕ	LUMEN PACKAGE	ССТ	COLOR
C-AR-A	<b>SQT7</b> Shoebox Style Floodlight	<b>17L</b> 16,900 Lumens 119W	<b>50K</b> Cool White (5000K) <b>40K</b> Neutral White (4000K)	<b>DB</b> Dark Bronze


**CERTIFICATIONS:** 







# **C-AR-A-SQT7 Series**



## **SERIES OVERVIEW**

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
16-1/5" L x 16-1/5" W x 3-4/5" H	18.0 lbs.	15 to 25 feet	N/A

## **FIXTURE SPECIFICATIONS**

HOUSING	Duraurable, die-cast aluminum housing with heat dissipating fins Dark bronze polyester powder-coat finish	
LENS ASSEMBLY	NEMA 7 optics for uniform light distribution	
MOUNTING	Fixture comes without mounting (sold separately) For use from 0°- 180° orientation Mounting sold separately and options available on page 3	

## **ELECTRICAL PERFORMANCE**

OPERATING MINIMUM	LIFESPAN L <sub>70</sub> at 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC Distortion	DIMMABLE
-40°C (-40°F)	Estimated >127,000 Hours	> 0.9	< 20%	No
INPUT VOLTAGE	120V	208V	240V	277V
CURRENT DRAW (Amps):	1.10A	0.63A	0.55A	0.47A

# **WARRANTY AND CERTIFICATIONS**

WARRANTY		UL LISTED	DLC	
	5 Year Limited*	Damp Locations	DLC Premium Qualified	



# **C-AR-A-SQT7 Series**

## **ACCESSORIES**



## PHOTOCELL - BUTTON, 120V/208V/240V/277V

SKU: C-ACC-A-PCELL-LV (120V)

**C-ACC-A-PCELL-HV-TL** (208V/240V/277V))

USE: Photocell is field installed. For use with 2" adjustable slip fitter only

### **MOUNTING OPTIONS**



#### **6" MOUNTING ARM**

SKU: C-ACC-A-SBMTARM-6IN-DB

USE: For pole mounting. For use only with C-AR-A-SQT Series



#### 2" SLIP FITTER

SKU: C-ACC-A-MTSL-2IN

USE: For pole mounting. Fits over 2-3/8" O.D. pipe



#### **ADJUSTABLE U-BRACKET**

SKU: C-ACC-A-AUB-DB

USE: For pole mounting. For use only with C-AR-A-SQT Series

© 2017 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Patent www.cree.com/patents. The CREE LEDs logo, C-LITE™ and the C-LITE logo are trademarks of Cree, Inc. The UL logo is a registered trademark of UL LLC. The DLC QPL Premium logo is a trademark of Northeast Energy Efficiency Partnerships, Inc.

