




BURNDY Catalog Number
UPC Number
Description
Status

KVS28
7818100623577
4/0R-4/0T CU 2BLT CONN
Active

Web Use
BURNDY Product Line



Product Description

General

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURIUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 250 in-lb

Conductor(s)

Aluminum Run Size (Range) N/A
Copper Tap Range 10 AWG-4/0 AWG
CopperWeld Solid Run Size (Range) 4/0
Copper Stranded Run (Range) 1/0 -4/0 AWG
CopperWeld Stranded Tap Size (Range) 3#12-7#6
CopperWeld Solid Tap Size (Range) 4/0
Aluminum Tap Size (Range) N/A
Galvanized Steel Size (Range) N/A
CopperWeld Stranded Run Size (Range) 7#8-7#6

Approvals / Certifications

UL Listed Y
CSA Certified Y
ROHS Compatible Compliant
UL Recognized N
CULUS N
Industry Standards RUS

Physical

Installation Torque 250
Type of Plating Unplated
Plated (Yes or No) N
Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175