


BURNDY Catalog Number

YA44L2TC38FX

UPC Number

7818100209999

Description

CU COMP.TERM-750 MCM FLE

Status

Active

Web Use

BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	4.74
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.33
B Length (in)	1.65
Pad Width (in)	2.19
E - in	1.00
Strip Length	1-5/8

General

Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 777.7 Flex, 1/2" Stud, 1" Stud Hole Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	750
Flex (Class H) Size - Range	750
Flex (Class I) Size - Range	750
Copper Solid Size (Range)	N/A
DLO Size (Range)	777.7 (1925/#24)
Copper Stranded (Range)	750

Physical

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Yellow
Plated (Yes or No)	Y
Index Number	L115
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175