



BURNDY Catalog Number
UPC Number
Description
Status

YA38LTC12FX
 7818100215699
 CU HYLUG-500 FLEX-1/2STD
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.41
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.45
Pad Width (in)	1.84
Strip Length	1-7/16

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 500 Flex, 1/2" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	500 kcmil
Flex (Class H) Size - Range	500 kcmil
Flex (Class I) Size - Range	500 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	535.3 (1325/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Pink
Plated (Yes or No)	Y
Index Number	L99
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175