

# N-GXE-POE-xx-01 Series

## PCIe Gigabit Ethernet Fiber Network Interface Card with PoE+

### 1000Base-X and 10/100/1000Base-T PoE+



The N-GXE-POE-xx-01 Series Network Interface Card (NIC) provides connectivity to a secure fiber network while also delivering power to a PoE powered device (PD), such as a VoIP phone with a copper UTP interface. It fully complies with all IEEE 802.3z and 1000Base-X standards, providing up to 2000 Mbps full-duplex bandwidth capacity.

Developed to support high-end users, this (2) port NIC has (1) 1000Base-X fiber network interface port (SFP version is 100/1000Base-X) and (1) switched 10/100/1000Base-T port supporting IEEE 802.3at PoE+ power. It is designed to allow a PC to power a VoIP phone, or any other traditional copper powered device, over a secure fiber network. Additionally, the NIC also has the ability to provide traffic switching functions between the copper and fiber ports, even when the PC is in a sleep mode.

Combining the functions of PC connectivity and VoIP phone connectivity into one device saves installation time, expense, and the space of having two devices at the desktop. When the VoIP traffic is filtered and prioritized by third-party devices like an Ethernet switch and the IP phone, this PoE NIC will pass all tagged traffic ensuring users experience a high level of quality of service. VLANs and Prioritization can also be configured at the NIC via Transition Networks' PoE NIC utility software.

## Features

- High bandwidth 1000Mbps
- Supports Full-duplex Mode
- Supports IEEE 802.3x Full-Duplex Flow Control
- Supports PCIe x1 bus
- Compliant with PCIe Rev 2.1 Interface
- Supports Jumbo Frames
- Supports High Level VLAN Filtering Function
- IPv6 Capable
- Supports IP headers and TCP/UDP checksum offload
- Wake-on-LAN (WoL) power management
- PXE 2.1 Boot ROM Supported
- ACPI 2.0 Link Status LED for each port
- Driver Support
  - Windows 7
  - Windows 8, 8.1
  - Windows 10
  - Windows Server 2008
  - Windows Server 2012
  - Windows Vista
- Available with a fixed LC port or SC or an open SFP port

## Specifications

Standards	IEEE 802.3-2000 IEEE 802.3z IEEE 802.3x IEEE 802.1Q IEEE 802.1p IEEE 802.3ab IEEE 802.3af IEEE 802.3at	
MAC Address	8k MAC address table	
Max Packet Size	Jumbo Frames, 10k bytes	
Jumper Switches	Legacy PoE Energy Efficient Ethernet (EEE) enable/disable	
Status LEDs	L/A PoE RJ-45 Upper Lf RJ-45 Upper Rt	Fiber Link/Activity Power-over-Ethernet TP Link/Activity/Speed TP Duplex
Dimensions	Width: 4.8" [121.9 mm] Depth: 6.5" [165.1 mm] Height: 0.9" [22.86 mm]	
Power Consumption	1.6 Watts (typical without PoE) 43.6 Watts (typical with PoE)	
Voltage input	PCIe 3.3V 12V Peripheral connection for PoE	
Power-over-Ethernet	Mode A Power	
Environment	Operating: 0°C to 50°C Storage: -15°C to 65°C Humidity: 5% to 95% (non-condensing) Altitude: 0 – 10,000 ft.	
Weight	2 lbs. [0.90 kg]	
Compliance	Emission: EN55022 Class B, CE, UL Listed Immunity: EN55024	
Warranty	Lifetime	



## Ordering Information

### N-GXE-POE-LC-01

1000Base-SX 850nm multimode LC  
[50/125 um fiber: 550 m/1804 ft.]  
[62.5/125 um fiber: 220 m/722 ft.]  
Link Budget: 8.0 dB  
Plus 10/100/1000Base-T PoE+ port  
(includes optional low-profile bracket)

### N-GXE-POE-SFP-01

Gigabit Ethernet PCIe NIC with a  
100/1000Base-X Open SFP fiber port, plus a  
10/100/1000Base-T PoE+ port  
(includes optional low-profile bracket)

### N-GXE-POE-SC-01(L)

1000Base-SX 850nm multimode SC  
[50/125 um fiber: 550 m/1804 ft.]  
[62.5/125 um fiber: 220 m/722 ft.]  
Link budget: 8.0dB  
Plus 10/100/1000Base-T PoE+  
(includes low-profile bracket only)

### N-GXE-POE-SC-01(S)

1000Base-SX 850nm multimode SC  
[50/125 um fiber: 550 m/1804 ft.]  
[62.5/125 um fiber: 220 m/722 ft.]  
Link budget: 8.0dB  
Plus 10/100/1000Base-T PoE+  
(includes standard bracket only)

## Optional Accessories

### SFP Modules

#### 27246

Cable assembly, 4 pin Molex to ATX Power  
Cable Adapter

#### 28582

4 pin Molex to SATA 15 pin Female Power  
Adapter

#### 28583

6" SATA Power Y Splitter Cable Adapter-M/F

### N-PoE-CBLKIT

3 piece cable kit for 12V power input  
connectivity options  
(Includes 27246, 28582, 28583)

### N-POE-EPC

Ethernet packet controller software utility used  
for VLAN configuration within the NIC. Free  
download from transition.com