

ALTV1224C4220

AC/DC CCTV Power Supply

Description

Altronix ALTV1224C4220 AC/DC Dual Output Power Supply is designed to provide both 12VDC and 24VAC outputs where a combination of both AC and DC outputs is required. It provides two (2) 12VDC outputs with a total current of 2A and two (2) 24VAC outputs with a total current of 4A.



ALTV1224C4220

Specifications

Input

Voltage 220VAC, 50/60Hz, 1.0A.

Outputs

Voltage 12VDC and 24VAC simultaneous.

Current 2A total @ 12VDC and
4A total @ 24VAC.

Outputs Ratings AC fuses: 3.5A / 250VAC.
DC fuses: 1A / 250VAC.

Indicators (LED)

Input 220VAC is present.

Output Output is powered.

Physical and Environmental

Dimensions (H x W x D)

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

Product Weight 14.5 lb. (6.58 kg).

Shipping Weight 15.4 lb. (7 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 72 BTU/Hr.