

VB6

Power Supply

Description

Altronix VB6 is a cost-effective 56VDC/30W UL Listed limited power supply. It is intended to power PoE related products such as the CAT5 to Coax cable Managed Ethernet Midspan receiver eBridge4PCR and the transceiver with integral managed PoE/PoE+ switch eBridge4SK. VB6 provides two sets of output terminals to facilitate connection for up to two devices. It is powered by a 24VAC/24VDC Class 2 rated transformer/power supply.



VB6

Specifications

Input

Voltage 24VAC @ 1.5A or 24VDC @ 1.5A.

Output

Voltage Two (2) 56VDC outputs with up to 30W combined total power.

Other Built-in overload protection.
Filtered and regulated.

Indicators (LED)

Input and Output LEDs.

Agency Listings

UL/cUL: Information Technology Equipment (UL 60950-1).

cUL: CSA Standard C22.2 No.205-M1983,
Signal Equipment.

CE European Conformity.

Physical and Environmental

Dimensions (L x W x H)

3.5" x 3.5" x 1" (88.89mm x 88.89mm x 25.4mm).

Product Weight 0.25 lbs. (0.11 kg).

Shipping Weight 0.3 lbs. (0.14 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 15 BTU/Hr.