



NG4access® Cabled Module, singlemode LC/UPC to stub, 24 fiber, microcable, 16 m

- Cabled modules enable the routing of fiber cable to the frame, where multiple connectors are terminated to the frame with a single click
- Integrated connectors ensure the cables are kept in sequential order, and help prevent accidental fiber breakage or disruption to adjacent fibers during installation
- Available in a pigtail version for splicing on frame or preterminated to 24-fiber microcable or conventional IFC cable

## Product Classification

|                              |                               |
|------------------------------|-------------------------------|
| <b>Brand</b>                 | NG4access®                    |
| <b>Product Series</b>        | NG4access                     |
| <b>Product Type</b>          | Fiber cabled module           |
| <b>Regional Availability</b> | Latin America   North America |

## Construction Materials

|                               |            |
|-------------------------------|------------|
| <b>Fiber Type</b>             | G.657.A2   |
| <b>Fiber Mode</b>             | Singlemode |
| <b>Total Fibers, quantity</b> | 24         |

## Dimensions

|                          |                     |
|--------------------------|---------------------|
| <b>Cable Stub Length</b> | 16 m   52 ft        |
| <b>Depth</b>             | 92.71 mm   3.65 in  |
| <b>Height</b>            | 13.21 mm   0.52 in  |
| <b>Width</b>             | 159.77 mm   6.29 in |

## Environmental Specifications

|                              |                                     |
|------------------------------|-------------------------------------|
| <b>Operating Temperature</b> | -5 °C to +40 °C (+23 °F to +104 °F) |
| <b>Relative Humidity</b>     | Up to 85%, non-condensing           |
| <b>Storage Temperature</b>   | -5 °C to +50 °C (+23 °F to +122 °F) |

## General Specifications

|                                     |          |
|-------------------------------------|----------|
| <b>Interface, front</b>             | LC       |
| <b>Total Ports, quantity, front</b> | 24       |
| <b>Interface Feature, front</b>     | Standard |
| <b>Color, front</b>                 | Black    |
| <b>Adapter Color</b>                | Blue     |
| <b>Adapters, quantity, front</b>    | 12       |

|                                 |                               |
|---------------------------------|-------------------------------|
| <b>Application</b>              | For use with NG4 panels       |
| <b>Body Style</b>               | Duplex   Straight orientation |
| <b>Cable Stub Type</b>          | Microcable                    |
| <b>Color, housing</b>           | Black                         |
| <b>Packaging Type</b>           | Bag   Carton                  |
| <b>Polarity</b>                 | Pairs, straight               |
| <b>Interface, rear</b>          | Stub tail                     |
| <b>Adapters, quantity, rear</b> | 1                             |
| <b>Color, rear</b>              | Black                         |
| <b>Package Quantity</b>         | 1                             |

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant