



NG4access® Cabled Module, singlemode LC/UPC to stub, 24 fiber, microcable, 46 m

- Cabled modules enable the routing of fiber cable to the frame, where multiple connectors are terminated to the frame with a single click
- Integrated connectors ensure the cables are kept in sequential order, and help prevent accidental fiber breakage or disruption to adjacent fibers during installation
- Available in a pigtail version for splicing on frame or preterminated to 24-fiber microcable or conventional IFC cable

Product Classification

Brand	NG4access®
Product Series	NG4access
Product Type	Fiber cabled module
Regional Availability	Latin America North America

Construction Materials

Fiber Type	G.657.A2
Fiber Mode	Singlemode
Total Fibers, quantity	24

Dimensions

Cable Stub Length	46 m 151 ft
Depth	92.71 mm 3.65 in
Height	13.21 mm 0.52 in
Width	159.77 mm 6.29 in

Environmental Specifications

Operating Temperature	-5 °C to +40 °C (+23 °F to +104 °F)
Relative Humidity	Up to 85%, non-condensing
Storage Temperature	-5 °C to +50 °C (+23 °F to +122 °F)

General Specifications

Interface, front	LC
Total Ports, quantity, front	24
Interface Feature, front	Standard
Color, front	Black
Adapter Color	Blue
Adapters, quantity, front	12

Application	For use with NG4 panels
Body Style	Duplex Straight orientation
Cable Stub Type	Microcable
Color, housing	Black
Packaging Type	Bag Carton
Polarity	Pairs, straight
Interface, rear	Stub tail
Adapters, quantity, rear	1
Color, rear	Black
Package Quantity	1

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant