

FDT-CJ048NXR1500



iFDT Indoor Fiber Distribution Terminal, 48-fiber, SC/APC, ribbon IFC cable, 1500 feet

- Compact and secure family of enclosures by connecting fiber cables at MDUs
- Integrated splice trays offer flexible splice management for individual or mass splicing
- Dual-hinged design ensures separation of owner/client network segments
- Robust steel construction protects fibers against damage and ensures network reliability
- Slotted cable entrance ports allow for rapid cable installation and pass-through capability

Product Classification

Product Type	Fiber distribution terminal
Product Series	iFDT
Regional Availability	North America

General Specifications

Adapters, quantity	48
Cable Type	IFC - Ribbon
Color	Putty white
Growth Configuration	Fully loaded
Interface Feature, input	APC
Interface, input	SC
Interface, stub	No connector
Package, quantity	1
Port, quantity	48

Dimensions

Cable Length	457.20 m 1500.00 ft
Depth	127.00 mm 5.00 in
Height	476.25 mm 18.75 in
Width	368.30 mm 14.50 in

Mechanical Specifications

Cable Entry Location	Bottom right Top right
Finish	Powder coated
Front Door Type	Double hinged
Lock Type	Padlock ready
Material Type	Steel
Mount Type	Wall

FDT-CJ048NXR1500

Optical Specifications

Fiber Mode Singlemode

Environmental Specifications

Environmental Space Indoor

Qualification Standard NEMA, Type 12 | Telcordia GR-2898-CORE

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant