

Quality Products. Service Excellence.

Horizontal Hinged Cable Manager PCMDD Series



Features

- · Constructed in 16-gauge steel.
- · Continuous hinged door with magnetic closure strip.
- Four oblong openings (3.5" x 1.56") top & bottom allowing for cable exit top and/or
- · Openings in the rear for cable entry.
- · Designed to fit standard 19" rails.
- Finished in textured black powder paint.
- · Requires mounting hardware.
- · RoHS and REACH compliant.
- · Manufactured in North America.



Help us improve the PCMDD Series

We're considering adding additional sizes. Would you prefer a deeper depth manager? *

- Current depth is fine
- Five (5) inch
- Seven (7) inch
- Greater than seven (7) inch

Gallery







Accessories

Mounting Hardware

	Ove	Overall Dimensions			Usable Dimensions		
Part No.	Height	Width	Depth	Units	Height	Width	Depth
PCMDD19001BK1	1.72	19.00	2.71	1U	1.25	17.62	2.50
PCMDD19003BK1	3.47	19.00	2.71	2U	3.00	17.62	2.50
PCMDD19005BK1	5.22	19.00	2.71	3U	4.75	17.62	2.50

Estimated Cable Fill Capa

Rack Description Contact our Technical Sales Team num Cable Fill (100% Fill Ratio)

Raits	Description	Qpantitg	RecCambreended Cable Fill (50% Editreatio)		Macairtism Cable Fill (100% Folk Flatio)		
Units		Quantity	Cat 5e	Cat 6a	Cat 5e	Cat 6a	
10	Channel Opening	1	34	15	68	30	
	Top/Bottom Opening	2 x 4 = 8	43	19	86	38	
	Rear Pass Through	0	n/a	n/a	n/a	n/a	
2U	Channel Opening	1	68	30	137	61	
	Top/Bottom Opening	2 x 4 = 8	43	19	86	38	
	Rear Pass Through	4	32	14	64	28	
3U	Channel Opening	1	103	46	207	92	
	Top/Bottom Opening	2 x 4 = 8	43	19	86	38	
	Rear Pass Through	4	32	14	64	28	

Cable fill capacity will vary based on the cable manufacturer.

Data subject to change without notice

 $\hbox{@ 2018.}$ Hammond Manufacturing Ltd. All rights reserved.

Contact our Technical Sales Team