



7000 SERIES PHOTOCONTROL

HIGH PERFORMANCE, LOW COST, UTILITY GRADE CONTROL

KEY FEATURES

- Multi-volt operation
- High-temperature housing and components
- 20mm, 15 kA, 480 Joule MOV Standard
- Reliable, versatile, high performance, and low cost
- Meets or exceeds ANSI C136.10

TE Connectivity's (TE) advanced technology 7000 Series Photocontrol provides a unique mix of low-cost, long-life, and multi-volt operation for demanding Roadway Lighting applications.


The 7000 Series Photocontrol unique design considerably improves the relay life. By surpassing 20,000 ON/OFF operations per the ANSI C136.10 standard, its expected life is 8-10 years.

Like all of our electronic controls, the 7000 Series utilizes our interlocking base/cap design for superior environmental protection.

IR Filtered Phototransistor gives a human eye response along with long-term, drift-free light sensing.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

7000 Series Photocontrol




The 7000 Series is the result of over fifty years of experience designing and delivering superior photocontrols and other lighting accessories in the US and around the world.

TECHNICAL INFORMATION

Rated Volts	05 - 305 VAC
Frequency	50/60 Hz
Operating Light Levels	Standard 1.5 Fc ON (optional 1 - 3 Fc)
Time Delay ON/OFF	Instant ON, 2 - 5 second delay OFF
OFF/ON Ratio	1.5 : 1
Fail Mode	ON
Surge Protection	20mm, 15 kA, 480 Joules MOV
Rated Life	8 years

Meets the CENELEC HD 629.1



ANSI Standard Cap Colors

120V	Gray
208 / 240 / 277V	Maroon
120 / 208 / 240 / 277V	Blue

SPECIFICATION

Physical	Dimensions: approx. 3.26" [83mm] dia. x 1.77" [45mm] high (not including contacts)
	Enclosure: designed to meet ANSI C136.10
	Power consumption: less than 0.5 watts at 120 VAC
Temperature	Minus 40°C to plus 65°C at 96% RH
Control	DC Electromagnetic switch type exceeds 20,000 ON/OFF operations per ANSI C136.10
Relay Rating	30 Amp General Purpose Relay
Load Rating	1000 Watt Tungsten 1800 VA
Light Sensor	Non-drifting Phototransistor
Cover	High impact polypropylene with UV stabilized polycarbonate window
Base	High temperature polyester (PBT)
Gasket	Cross-linked polyethylene
Connection	3-pole locking-type with solid brass legs

HOW TO SPECIFY

The 7000 series offers almost unlimited options ensuring your lighting network needs will be met.

7 0 90 - V P S - _ _

Series (Fail Mode)

7 = 7000 (ON)

OFF/ON Ratio

0 = 1.5 : 1

Voltage

60 = 120
72 = 208/240/277
90 = 120/208/240/277

MOV Surge Protection

V = 480J, 320V, 15,000A, 20mm

Cap Color

(Leave blank if ANSI Standard)

BL = Blue
BK = Black
BR = Brown (Bronze)
GN = Green
GR = Gray
MR = Maroon
YL = Yellow

Turn-On Level

1 = 1.0 Fc
S = 1.5 Fc (ANSI Std)
2 = 2.0 Fc
3 = 2.6 Fc

Light Sensor

P = Phototransistor
F = IR Filtered Phototransistor

te.com/energy

©2011, 2012, 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. 4-1773453-5 E324 10/2014

TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 896 089 903
Spain:	+ 34 916 630 400
Benelux:	+ 32 16 351 731
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
China:	+ 86 (0) 400-820-6015