# Vi2201

### MaxiiPower™ Single Port 802.3at, 30W Midspan

#### **Features**

- Cost effective single port 802.3at 30W compliant PoE power supply for 10/100/1000Base-T networks
- · Built-in 30W power supply
- Delivers up to 30W for high power applications
- Complies with 802.3 safety standards for automatic detection and over-current protection
- Provides high data rate and power for Megapixel IP camera applications
- Tested to RFC 2544 packet transmission standards
- Compact design
- Limited lifetime warranty



## **Applications**

- Local PoE source for IP cameras
- Cost effective solution for applications using non-PoE network switch
- Powering all types of PoE pwered IP equipment

Vigitron's MaxiiPower™ Vi2201 is a high power single port Midspan compliant to IEEE 802.3af/at. It is a cost effective solution for powering a wide range of IP cameras that offers all standard PoE safety features including detection, connection/disconnection and fault protection. With a transmission bandwidth of up to 1Gbps, its application has virtually no bandwidth limitations and interfaces with the highest megapixel cameras.

The Vi2201 includes a built-in power supply and does not require an external power supply. The Vi2201 is compact size, easy to install and ideal for using in environmental enclosures or other space restricted applications.

The Vi2201 complies with all network transmission standards and is an ideal solution for powering any PoE device that requires high power PoE.

# **Application Diagram**







# **Technical Specification**

#### **Electrical**

Ethernet Interface Standard 10/100/100BaseT UTP Category 5 (or higher)
PoE Output 30W @ 53V DC Input Power 100-240VAC, 50/60Hz

Status LEDs Power

PoE Active

PoE Power Pins 4&5 (+), 7&8 (-)
Connectors Input: Shielded RJ-45

Output: Shielded RJ-45

Main Power IEC 320 C5

Management Auto PoE Detection

Regulatory CE, FCC, WEEE, RoHS (G0545530060PSE1000)

#### **Environmental**

Humidity 20 to 85%, non-condensing

Temperature Operating: 0°C to +40°C

Storage: -10°C to +70°C

#### **Mechanical**

Dimensions 4.53 x 2.45 x 1.32 in., 115 x 62 x 34 mm (LxWxH)

Weight 0.42 lb (190g) Material Plastic Case

#### **Accessories**

Molded IEC 7 ft. (200cm) Power Cord (included)

### **Ordering Information**

Part No. Description

Vi2201 | Single Port 802.3at, 30W PoE Midspan

## **System Configuration**









