## SI-IES-1200-LRT

# **Unmanaged Hardened PoE+ Injector**

## (1) 10/100/1000Base-T Port + (1) 10/100/1000Base-T PoE+ Port

**Specifications** 

Standards

Compliance

Warranty



The SI-IES-1200-LRT is an unmanaged hardened PoE+ injector that adds up to 30 Watts of power on a network segment. Injectors are commonly used to power PoE devices in locations where a power source does not exist. The injector has redundant input power connections, and a fault alarm relay to ensure safe reliable operation in temperatures between -40°C and +75°C.

Transition Networks' hardened PoE injectors are certified to operate reliably in harsh environments such as those found on factory floors, outdoor enclosures or other challenging environments.

## **Ordering Information**

#### SI-IES-1200-LRT

(1) 10/100/1000Base-T port + (1) 10/100/1000Base-T PoE+ port

Optional Accessories (sold separately) **Industrial Power Supplies:** 

Input: 85-264VAC, 120-370VDC Output: 48VDC, .83A, 39.8 Watts

### **Features**

- IEEE 802.3at PoE+ to supply 30 Watts
- Supports IEEE 802.3af
- Non-blocking architecture
- Compact size
- IP30 housing protection
- Link Pass Through
- Extended operating temperature (-40°C to 75°C)
- DIN Rail mount / optional wall mount brackets included

#### IEEE 802.3at IEEE 802.3af (1) DATA IN RJ-45 Ethernet Port Connectors (1) DATA OUT PoE+ RJ-45 Ethernet Port 30 Watts Status LEDs PWR1 (Power): ON=primary power PWR2 (Power): ON=backup power connected Width: 1.2" [30 mm] Depth: 3.7" [95 mm] Dimensions Height: 5.5" [140 mm] Power Consumption 3.53 Watts (No PoE) 33.36 Watts (1 port PoE) Power Input 24-48VDC IP30 Ingress Protection Environment Operating: -40°C to 75°C Storage: -40°C to 85°C Humidity: 5% to 95% (non-condensing) Altitude: 0 - 10,000 ft. Weight

1.3 lbs. [0.59 kg]

FCC Class A, CE Mark, EN61000-4, EN61000-6-2. EN61000-4-2 (ESD). EN61000-4-3 (RS), EN61000-4-4 (EFT) EN61000-4-5 (Surge), EN61000-4-6(CS) EN61000-4-8 (Magnetic Field), IEC60068-2-27(Shock), IEC60068-2-32 (Free fall). IEC60068-2-6 (Vibration)

Safety: UL508

Lifetime

IEEE 802.3 IEEE 802.3u

IEEE 802.3ab