

## 3FT RAPIDRUN®; DIGITAL DVI-D&TRADE; PASSIVE FLYING LEAD

42414 | [C2G](#)


### FEATURES & BENEFITS

**DISCONTINUED** RapidRun® Digital is designed to be the standard for in-wall digital audio/video installations. The RapidRun system empowers you to customize your installation to create your own ideal audio/video solution. Break-away flying leads and wall plates ensure flexible, efficient, high quality connections for all types of equipment.

#### Electrical characteristics

- Impedance: 100±10Ω
- DC resistance: DC300V
- Velocity of propagation: 78±1%
- Insulation resistance: 93.25Ω/km at 20°C max.

#### Physical characteristics

- Voltage rating: 30V
- Temperature rating: 75°C
- Operating temperature range: -40° - 75°C
- Minimum bend radius: 90mm

#### Conductor (qty. 1 pair and 5 conductors)

- Conductor type: 24AWG (7/0.20)(tinned copper)
- Insulation: HD-PE

#### Conductor type (qty. 4 pair)

- Conductor type: 28AWG (7/0.20)(silver plated copper)
- Insulation: Foam PE SKIN
- Shield: Aluminum foil (100% coverage)
- Drain wire: 24AWG (7/0.20)

#### DVI-D connector

- Connector type: 18+1 DVI-D Single Link
- Gender: Male
- Contact material: Brass, 5µm gold plating
- Insulation: Black PBT

#### RapidRun connector

- Connector type: 19-pin DIN
- Gender: Male
- Contact material: Brass, 15µm gold plating
- Insulation: Black PBT

### SPECIFICATIONS

#### GENERAL INFO

Discontinued: Yes  
Color: Black

Product Series: RapidRun  
Type: RapidRun Digital Flying Leads