



6FT RAPIDRUN®; DIGITAL DVI-D & TRADE; + 3.5MM AUDIO PASSIVE FLYING LEAD

42433 | [C2G](#)

FEATURES & BENEFITS

DISCONTINUED RapidRun® is designed to be the standard for in-wall audio/video installations. The RapidRun system empowers you to customize your installation to create your own ideal audio/video solution. Break-away flying leads and wall plates ensure flexible, efficient, high quality connections for all types of equipment.

Electrical characteristics

- Impedance: $100 \pm 10 \Omega$
- DC resistance: DC300V
- Velocity of propagation: $78 \pm 1\%$
- Insulation resistance (500V): $93.25 \Omega/\text{km}$ at 20°C max.

Physical characteristics

- Voltage rating: 30V
- Temperature rating: 75°C
- Operating temperature range: $-40^\circ - 75^\circ\text{C}$
- Minimum bend radius: 90mm

Conductor (1 pair and 5 conductors)

- Conductor type: 24AWG (7/0.20)(tinned copper)
- Insulation: HD-PE

Conductor (4 pair)

- Conductor type: 28AWG (7/0.20)(silver plated copper)
- Insulation: Foam-PE SKIN
- Shield: Dual Aluminum Foil (100% coverage)
- Drain wire: 24AWG (7/0.20)(tinned copper)

Overall cable

- Foil shield: Aluminum foil (100% coverage)
- Braided shield: 24/12/0.10 (85% coverage)(tinned copper)
- Drain wire: 24AWG (7/0.20)(tinned copper)
- Jacket: PVC-CL2 rated

DVI-D connector

- Connector type: 18+1 DVI-D Single Link
- Gender: Male
- Contact material: Brass, $5\mu\text{m}$ gold plating
- Insulation: Black PBT

RapidRun connector

- Connector type: 19-pin DIN
- Gender: Male
- Contact material: Brass, $15\mu\text{m}$ gold plating
- Insulation: Black PBT

SPECIFICATIONS

GENERAL INFO

Discontinued: Yes

Color: Black

Product Series: RapidRun

Type: RapidRun Digital Flying Leads