


Fan-Out Tight-Buffered Cable, Plenum 2 F, 2.0 mm Subunits, Single-mode (OS2)

CORNING

Part Number: 002E68-31331-29

Corning fan-out plenum cables are designed for use in building backbone and horizontal cabling. These multifiber cables use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are stranded around a dielectric central member with a flame-retardant outer jacket, making this cable particularly useful for applications requiring direct connection to terminal equipment or requiring extra rugged cables.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.



Features and Benefits

900 μm buffered fibers

Easy, consistent stripping

Temperature- and water-resistant

Superior protection

All-dielectric construction

Requires no grounding or bonding

Fan-Out Tight-Buffered Cable, Plenum 2 F, 2.0 mm Subunits, Single-mode (OS2)

The CORNING logo is displayed in white, uppercase letters on a dark blue rectangular background.

Specifications

Mechanical Specifications

Max. Tensile Strength, Long-Term	132 N
Max. Tensile Strength, Short-Term	440 N
Min. Bend Radius Installation	87 mm (3.43 in)
Min. Bend Radius Operation	58 mm (2.28 in)
Nominal Outer Diameter	5.8 mm (0.23 in)

Cable Design

Central Element	Yarn
Fiber Count	2
Number of Ripcords	1
Outer Jacket Color	Yellow
Outer Jacket Material	Flame-retardant
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Tensile Strength Elements and/or Armoring - Layer 2	Dielectric strength members
Number of Subunits	2
Subunit Color	Yellow
Subunit Diameter	2 mm (0.08 in)
Subunit Jacket Material	Flame-retardant
Tight Buffer Color	White
Flame Rating	Plenum (OFNP)

Fan-Out Tight-Buffered Cable, Plenum 2 F, 2.0 mm Subunits, Single-mode (OS2)

CORNING

Environmental Conditions

Temperature Range, Installation	0 °C - 60 °C (32 °F - 140 °F)
Temperature Range, Storage	-40 °C - 70 °C (-40 °F - 158 °F)
Temperature Range, Operation	0 °C - 70 °C (32 °F - 158 °F)

General Specifications

Environment	Indoor
Cable Type	Tight-Buffered
Product Type	Distribution
Fiber Category	Single-mode (OS2)
Flame Rating	Plenum (OFNP)
Application	General Purpose Horizontal , Vertical Riser , Plenum

Ordering Information

Weight	33 kg/km
--------	----------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	National Electrical Code® (NEC®) OFNP, CSA FT-6, ICEA S-83-596
Flame Test Method	UL-1666 (for riser and general building applications)

Optical Characteristics

Fiber Code	E
------------	---

Fan-Out Tight-Buffered Cable, Plenum 2 F, 2.0 mm Subunits, Single-mode (OS2)

CORNING

Optical Characteristics

Fiber Name	SMF-28e+® fiber
Fiber Type	Single-mode
Performance Option Code	31
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.4 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Category	G.652.D



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.