


LSZH™ Loose Tube, Gel-Free, Single-Jacket Cable 24 F, Single-mode (OS2)

CORNING

Part Number: 024EUZ-T4101D20

Corning LSZH™ loose tube gel-free cables are flame-retardant, indoor/outdoor, suitable for installation in interbuilding and intrabuilding applications. The loose tube design offers mechanical ruggedness and environmental durability while the all-dielectric cable construction requires no grounding or bonding. The water-swallowable yarn eliminates the need for gel-filling compound and allows more efficient and craft-friendly cable preparation. The 250 µm color-coded fibers allow quick and easy identification during installation.

Corning LSZH™ cables eliminate risks in the event of a fire as the LSZH compound does not drip when superheated. The material burns to ash, eliminating the onset of secondary fires. When cables containing halogens ignite, they emit highly reactive gases that can be harmful if inhaled. When halogens combine with water, acids are formed. These acids damage both living tissue and inorganic materials, such as metal and electronic equipment. The flexible, flame-retardant outer jacket is UV-resistant and enables direct exposure to sunlight. Interlocking armor is available for special applications requiring additional mechanical durability.



Features and Benefits

Low-smoke, zero-halogen sheath

Key life-safety benefit

Meets cyclic impact and chemical resistance test

Superior performance

Common installations

Outdoor aerial and duct; indoor general purpose horizontal according to NEC Article 770

LSZH™ Loose Tube, Gel-Free, Single-Jacket Cable 24 F, Single-mode (OS2)

CORNING

Specifications

Mechanical Specifications

Max. Tensile Strength, Long-Term	810 N
Max. Tensile Strength, Short-Term	2700 N
Min. Bend Radius Installation	192 mm (7.56 in)
Min. Bend Radius Operation	128 mm (5.04 in)
Nominal Outer Diameter	12.8 mm (0.5 in)

Cable Design

Central Element	Dielectric
Fiber Count	24
Buffer Tube Color Coding	Blue, Orange
Number of Ripcords	2
Outer Jacket Color	Black
Outer Jacket Material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Buffer Tube Color	Blue, Orange
Buffer Tube Diameter	2.5 mm (0.1 in)
Number of Active Tubes	2
Number of Filling Elements	4
Number of Tube Positions	6
Tape	Water-swellaable
Tape, Layer 2	Flame-retardant tape
Tape, Layer 3	Water-swellaable

LSZH™ Loose Tube, Gel-Free, Single-Jacket Cable 24 F, Single-mode (OS2)

CORNING

Cable Design

Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
----------------	--

Fibers per Tube	12
-----------------	----

Environmental Conditions

Temperature Range, Installation	-30 °C - 60 °C (-22 °F - 140 °F)
---------------------------------	----------------------------------

Temperature Range, Storage	-40 °C - 70 °C (-40 °F - 158 °F)
----------------------------	----------------------------------

Temperature Range, Operation	-40 °C - 70 °C (-40 °F - 158 °F)
------------------------------	----------------------------------

General Specifications

Environment	Indoor/Outdoor
-------------	----------------

Cable Type	Loose Tube
------------	------------

Product Type	Dielectric
--------------	------------

Fiber Category	Single-mode (OS2)
----------------	-------------------

Flame Rating	LSZH™ (OFN-LS)
--------------	----------------

Application	Aerial , Direct Buried , Duct , General Purpose Horizontal
-------------	--

Ordering Information

Weight	152 kg/km
--------	-----------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

LSZH™ Loose Tube, Gel-Free, Single-Jacket Cable 24 F, Single-mode (OS2)

CORNING

Standards

Approvals and Listings National Electrical Code® (NEC®) OFN-LS, Sunlight Resistant (SUN RES), IEEE-1202 flame test, Suitable for Direct Burial (DIR BUR), IEC 60332-3, IEC 60754-2, IEC 61034

Design and Test Criteria ANSI/ICEA S-104-696, UL 13, UL 444, UL 1277, UL 1685, CSA C22.2, No. 230 and No. 232, CSA OFC (FT-4-S1)

Optical Characteristics

Fiber Code E

Fiber Name Single-mode (OS2)

Fiber Type Single-mode

Performance Option Code 01

Maximum Attenuation 0.4 dB/km / 0.4 dB/km / 0.3 dB/km

Wavelengths 1310 nm / 1383 nm / 1550 nm

Fiber Category G.652.D



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.