MS2™ Super Mate Module Dry Transparent



Part Number: 80610416218

The MS²™ Super Mate Module Dry Transparent 4005-DPM/TR is a 25-pair modue that features an array of U-shaped, phosphor-bronze contacts and stainlesss steel cut-off blades. This is a dry, pluggable module with a transparent cover that's designed for use in aerial, buried, central office and underground applications. It is suggested to use one of the MS²™ Splicing Rigs along with this product.

MS2™ Super Mate Module Dry Transparent



Specifications

| Design | |
|----------------|-------------------------------------|
| Composition | Dry |
| Pair Count | 25 |
| Sealing Type | Free-Breathing, Sealed Encapsulated |
| Connector Type | Straight, Pluggable Bridge |
| Closure Type | Free-Breathing, Sealed Encapsulated |
| Conductor | 28 - 22 AWG |

| Mechanical Specifications | |
|---------------------------|-----|
| Connection | IDC |

| General Specifications | |
|------------------------|------------------|
| Product Type | Modules |
| Cable Type | PIC, Pulp, Paper |

| Dimensions | |
|------------|--------------------|
| Length | 164.5 mm (6.48 in) |
| Height | 9.1 |

| Standards | |
|------------------|----|
| Flame Retardance | No |

MS2™ Super Mate Module Dry Transparent





Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.