Single Cassette Housing (SCH) Wallmountable, holds one CCH Splice Cassette, black



Part Number: SCH-01C

Corning single-cassette housing is a costeffective option for storage, protection and termination of optical fiber cables in applications with minimal mounting space. The housing accepts standard LANscape® solution closet connector housing (CCH) cassettes, and offers protection for the fiber cable and connectors for indoor wall-mountable installations.

This compact unit is optimized for use in locations such as Box-in-a-Box applications, building entrances, terminals, wiring closets, open office and other areas where space is a premium. The durable black metal housing can be used with either CCH pigtailed splice cassettes, standard CCH splice cassettes or CCH field termination cassettes with Unicams®, and be utilized for splice management, crossconnector or both for up to 24 single-fiber heat-shrink splices or 2 ribbon heat-shrink splices, if so desired.



Features and Benefits

Small wall-mount housing for pre-term or field term

Minimal mounting space required; Box-in-a-Box

Metal housing with smooth, black powder coat finish

Durability with better label adhesion

LANscape® Solutions

Complexity reduction and CCH splice cassette availability

Single Cassette Housing (SCH) Wallmountable, holds one CCH Splice Cassette, black



Specifications

Design	
Cable Entry Direction	Top / Bottom
Panel or Module Type	CCH Splice Cassette
Housing Type	Wall-Mountable Hardware

General Specifications	
Access Type	Front access
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware
Application	Enterprise Networks

Dimensions	
Height	16.84 cm (6.57 in)
Width	31.75 cm (12.38 in)
Depth	6.68 cm (2.61 in)

Shipping Dimensions		
Height	20 cm (7.8 in)	
Width	38.7 cm (15.09 in)	
Depth	10.1 cm (3.94 in)	

Single Cassette Housing (SCH) Wallmountable, holds one CCH Splice Cassette, black



Connector Specs	
Housing Color	Black
Ordering Information	
Weight	1.5 kg
Shipping Weight	2.09 kg

1/1

Standards

Units per Delivery

RoHS Free of hazardous substances according to RoHS 2011/65/EU



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.