

Integrated Single-Panel Housing 12 F, bottom-mounted OptiTip® adapters, front-mounted LC duplex adapters, UPC, Single-mode (OS2)

CORNING

Part Number: SPH-12OTR-12A9H

Corning Integrated single-panel housing utilizes the OptiTip® adapter with the small-profile single-panel housing for quick and easy deployment eliminating the need for field-terminated and strain-relieved fiber optic cables. The housing is ideal for star, ring, point-to-point, or zone architectures. Factory-terminated panels provide industry-leading quality and reliability while eliminating the time required for field-termination methods and the need for specialized field-termination tools, training, and specially prepared locations. The compact unit is ideal for use inside NEMA- and IP rated enclosures and other environments where space is a premium.

Many of our fiber optic hardware products are highly configurable. If you don't see what you are looking for here, please review the ordering matrix contained in the family spec sheet found on the right, or contact Customer Care at 1-800-743-2675.



Features and Benefits

Factory terminated

Eliminates need for field termination, improving reliability and speed of deployment; faster, easier installation and moves, adds and changes

Configurable in 12 and 24 fibers, single-mode and multimode, supporting SC, LC and ST® compatible connectors

Network flexibility

Integrated Single-Panel Housing 12 F, bottom-mounted OptiTip® adapters, front-mounted LC duplex adapters, UPC, Single-mode (OS2)

CORNING

Specifications

Design - Adapter

Adapter Style	Standard
Adapter Type	LC duplex

Design

Fiber Count	12
Polish	UPC
OptiTip® Adapter Placement	Bottom-mounted
Housing Type	AnyLAN Housings and Modules

General Specifications

Fiber Category	Single-mode (OS2)
Mounting Type	Wall-Mountable
Product Type	AnyLAN Housings and Modules
Application	Enterprise Networks

Cable Design

Fiber Count	12
-------------	----

Dimensions

Height	16.5 cm (6.44 in)
Width	15.2 cm (5.93 in)

Integrated Single-Panel Housing 12 F, bottom-mounted OptiTip® adapters, front-mounted LC duplex adapters, UPC, Single-mode (OS2)

CORNING

Dimensions

Depth	3.8 cm (1.48 in)
-------	------------------

Connector Specs

Connector Type	LC duplex
----------------	-----------

Specifications - Connector A

Polish	UPC
--------	-----

Ordering Information

Package Contents	Housing; installation guide; label, unit ID; 2 mounting brackets; 2 screws, 10-32 x .25; 2 screws, 8-18 x .625; 4 screws, 6-32 x .25 and 4 screws, 6-32 x .312
------------------	--

Shipping Weight	0.7 kg
-----------------	--------

Units per Delivery	1/1
--------------------	-----



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.