

CCH Pigtailed Splice Cassette 12 F, LC duplex, aqua, 50 µm multimode (OM4)

CORNING

Part Number: CCH-CS12-E4-P00QE

CCH pigtailed splice cassettes enable faster field splicing and easy modular management of connectorization within the housing. The CCH pigtailed splice cassettes are preloaded and pre-routed for quick fusion splicing of either individual or ribbon fiber pigtails, using the same space-saving platform as the standard CCH splice cassette.

The pre-routed pigtailed cassettes reduce field labor by streamlining the features and components of the pigtail cassette to allow for efficiencies in the field. They are prepped with a 2 meter pigtail assembly with all pre-existing CCH panel connector options. The pigtailed cassettes have 900 µm at the connector panel for added durability and colored 250 µm for ease of splicing as well as having strain relief pre-applied to the assemblies from the manufacturing facility.

With the pigtailed cassette, the field will also enjoy the elimination of individual splice trays or separate splice housings, as well as allowing splicing to be done away from the rack housing in a suitable workspace as needed. The modular design makes it easy to access the fiber in an individual cassette without disturbing the other fibers in the housing.

Each cassette is shipped with the pigtailed CCH adapter panel of choice, one rail for use with CCH-01U/2U/3U housings, and two rails used with CCH-04U housings. Grommets and cable ties for additional strain relief and protective braided tubing for incoming cable are also included. Splicing cassettes ship with the appropriate quantity and type of heat-shrink splice protectors.

Many of our products are highly configurable. If you don't see what you are looking for, review



Features and Benefits

Manage cable slack for a CCH panel in a modular footprint

Fast, easy and reliable initial routing, and quick, simple reaccess for moves, adds and changes (MACs)

Includes everything needed to convert a CCH housing for modular routing and/or splicing

Easy ordering and field installation

Modular splice capability

Manage all splices inside the housing

900 µm jacket at the connector panel

Added fibre protection at the connector

Colored 250 µm at splice point

Easy to identify and prep colored 250 µm for fast and easy splicing

Pre-prepped splice cassette

Saves time in the field with a ready to splice product

Broad operating temperature range (-40°C to +75°C)

Utility and flexibility

CCH Pigtailed Splice Cassette 12 F, LC duplex, aqua, 50 µm multimode (OM4)

CORNING

Specifications

Design - Adapter

Adapter Type	LC duplex
--------------	-----------

Design

Fiber Count	12
Connector Configuration	LC duplex
Panel or Module Type	CCH
Splice Protectors Type	Heat Shrink Splice Protection
Number of Splice Protectors	12

General Specifications

Product Type	Rack-Mountable Hardware
Fiber Category	50 µm MM (OM4)
Cable Type	250 µm
Technology	Fusion Splice
Mounting Type	CCH Housings , Wall-Mountable
Application	Data Center , Enterprise Networks

Cable Design

Fiber Count	12
-------------	----

CCH Pigtailed Splice Cassette 12 F, LC duplex, aqua, 50 µm multimode (OM4)

CORNING

Dimensions

Height	35
Width	162
Depth	200

Ordering Information

Units per Delivery	1/1
--------------------	-----

Environmental Conditions

Temperature Range, Operation	-40 °C - 65 °C (-40 °F - 149 °F)
------------------------------	----------------------------------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	Meets ANSI/TIA/EIA-568A and 606 Tested in accordance with Telecordia GR-3125, UL1863 - Communication Circuit Accessories



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea