

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com


USB-C Dock, Dual Display - 4K HDMI/DP, VGA, USB 3.2 Gen 1, USB-A/C Hub, GbE, 100W PD Charging, Silver

MODEL NUMBER: U442-DOCK4-S











USB-C docking station with PD Charging adds HDMI, VGA, DP, USB 3.2, Ethernet and audio ports to your Windows laptop or PC.

Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a Workstation

This USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting digital audio and video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device, connecting to a Gigabit Ethernet network and a lot more—all at the same time.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video Signals

By connecting the detachable USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K Video and Digital Audio

The HDMI and DisplayPort (DP) outputs support Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. The VGA port supports HD resolutions up to 1920 x 1200, including 1080p, at 60 Hz. A Mini DisplayPort or DVI display may also be connected using a DP to mDP or HDMI to DVI adapter (sold separately).

DisplayPort Multi-Stream Transport (MST) Allows Connection of Multiple Displays

By connecting the detachable USB-C cable to a source that supports DisplayPort MST Mode, you may connect two displays simultaneously. This allows you to display the same image on both monitors, extend your host desktop across both with different windows open on each, or combine both into one large display as a video wall. Connect dual monitors in Extended (4K @ 30 Hz DP with 1080p HDMI or 720p VGA) and Mirror (1080p DP with 1080p HDMI or 1080p VGA) modes. HDMI and VGA video ports will not work simultaneously.

USB Ports Connect Keyboards, Thumb Drives and Other Peripherals

One USB-C and four USB-A hub ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support fast USB 3.2 Gen 1 data transfer rates up to 5 Gbps (10 times faster than USB 2.0) and are backward compatible with USB 2.0 and USB 1.1 devices. Two ports also support BC 1.2 charging with 5V 1.5A (7.5W) of power dedicated to fast-charging your mobile device.

PD Charging Port Charges the Connected Notebook, Tablet or Other Device

Highlights

- Connects 2 displays at the same time for easy multitasking and increasing productivity
- Supports Ultra HD 4K resolutions up to 3840 x 2160 @ 30 Hz for crystal-clear video
- Joins a wired 10/100/1000
 Gigabit Ethernet network when no Wi-Fi is available
- Supports 20V 5A (100W) power output for fast-charging largecapacity mobile devices
- USB-C and USB-A data ports allow connection of flash drives and other peripherals

Applications

- Extend or mirror your laptop or PC monitor on multiple displays to aid in multitasking and increase productivity
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Save data to a USB-enabled thumb drive or external hard drive
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Connect a microphone/headset to record a podcast or listen to music

System Requirements

• Source device with USB-C or



The USB-C port supports Power Delivery (PD) 2.0 charging of connected PD Charging-compliant devices, such as laptops, Kindles, iPads and Android smartphones. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 5A (100W). This port, as mentioned above, can also be used for transferring data up to 5 Gbps.

Accesses a Wired Gigabit Ethernet Network

The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Connects Speakers, Microphone and Other Audio Equipment

The USB-C hub's 3.5 mm mini stereo jacks are convenient for connecting speakers, headphones or a microphone to your workstation. You can listen to music or record the latest episode of your podcast.

Detachable USB-C Cable Connects in Either Direction

Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

Ready to Use Right Out of the Package

The plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. It's slightly larger than an average smartphone, but compact enough to fit easily into your desk space without taking up much valuable room.

Thunderbolt 3 port that supports
USB DisplayPort Alternate
Mode

- Display device with DisplayPort,
 HDMI, VGA, Mini DisplayPort*
 or DVI* input
- Not for use with Thunderbolt monitors
 *Requires adapter (sold separately)

Package Includes

- U442-DOCK4-S USB-C Dock,
 Dual Display, Silver
- USB-C cable (M/M), 2.6 ft.
- External power supply (Input: 100–240V, 50/60 Hz, 1.8A; Max Output: 20V 3.6A)
- Owner's manual

Specifications

| OVERVIEW | | |
|--|---|--|
| UPC Code | 037332213518 | |
| INPUT | | |
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 1.8A | |
| External Power Supply Output Specs (V / A) | 20V / 3.6A | |
| External Power Supply Cord Length (ft.) | 4.0 | |
| External Power Supply DC Barrel Connector Specs | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve | |
| External Power Supply Plug(s) | NEMA 1-15P North America | |
| External Power Supply Certifications | CE; RoHS; UL; cUL | |
| Bus Powered | No | |



| BATTERY | |
|--|---|
| Battery Charging (1.2 Port) | Yes |
| CHARGING | |
| Charging Ports / Amps | 0.9A; 1.5A; 5A |
| USB Power Delivery (PD) Charging Support | Yes |
| Charging Watts | 100 |
| USB Power Delivery (PD) Charging Specification | 2.0 |
| PHYSICAL | |
| Cable Jacket Rating | VW-1 |
| Color | Silver |
| Material of Construction | PVC, Aluminium |
| Shipping Dimensions (hwd / in.) | 2.30 x 9.45 x 7.90 |
| Shipping Weight (lbs.) | 2.55 |
| Unit Dimensions (hwd / in.) | 0.87 x 7.8 x 3.3 |
| Unit Packaging Type | Box |
| Unit Weight (kg) | 0.43 |
| Unit Weight (lbs.) | 0.94 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 113 F (0 to 45 C) |
| Storage Temperature Range | 14 to 158 F (-10 to 70 C) |
| BTUs | 34.1 BTU/Hr |
| Power Consumption (Watts) | 10 |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing |
| Storage Humidity Range | 5% to 90% RH, Non-Condensing |
| Power Provided to Connected Device(s) | 5V 0.9A Output (USB A), Up to 20V 5A (100W) Input (USB C) |
| COMMUNICATIONS | |
| Network Speed | 1Gbps |
| IEEE Standards Supported | 802.3; 802.3u; 802.3az; 802.3x |
| CONNECTIONS | |
| Ports | 13 |





| Side A - Connector 1 | 3.5MM (FEMALE); (2) USB 3.0 A (FEMALE); USB C (FEMALE) |
|--|---|
| Side B - Connector 1 | 3.5MM (FEMALE); DISPLAYPORT (FEMALE); HD15 (FEMALE); HDMI (FEMALE); RJ45 (FEMALE); (2) USB 3.0 A (FEMALE); USB C (FEMALE) |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| Max Supported Video Resolution | DP/HDMI: 3840 X 2160 (4K X 2K) @ 30HZ; VGA: 1920 X 1200 (1080P) @ 60HZ |
| Displayport Specification | 1.2 |
| HDMI Specification | 1.4 |
| HDCP Specification | 1.4 |
| USB Specification | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |
| Audio Specification | Stereo |
| Driver Required | No |
| Recommended Category Cable | Cat5/Cat5e/Cat6 Cables |
| Auto MDIX Support | Yes |
| Full Duplex Support | Yes |
| Suspend Mode Support | Yes |
| Remote Wakeup Support | Yes |
| Technology | Cat5/5e; Cat6; DisplayPort; HDMI; Stereo Audio; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); VGA/SVGA; PD Charging |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies