







## PN1A-32X16F

 $32\ \mathrm{Ch}\ \mathrm{NVR}$  with  $16\ \mathrm{Plug}\ \&\ \mathrm{Play}$  Ports, True Facial Recognition,  $256\ \mathrm{Mbps}$  ,  $8\ \mathrm{HD}\ \mathrm{Bays}$  ,  $4\mathrm{K}$ 

## Standard Features

- Up to 8 Megapixel Resolution Recording
- True Facial Recognition Capable with Compatible Camera
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- True P2P Connectivity with QR Code Connect
- Multiple video search options including Analytic and Thumbnail Search for quick retrieval of footage.
- H.265/H.264 Video Compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

System	
Compression	Standard H.265
OS	Embedded Linux
Video	
Network Input	32 Ch IPC Input - 16 PnP PoE Ports
Network Access Bandwidth	256 Mbps
Network Access Format	8 MP, 5MP, 4 MP, 3 MP, 1080p, 960p, 720 @25, 30 FPS
Output	HDMI x 1: 4K / 2K / 1920x1080 / 1280x1024 VGA x 1: 1920x1080 / 1280 x 1024 (ability to independently split, making the VGA a call monitor, no mouse control)
Audio	
Network Input	32 Channel IPC Audio Input
2-Way Audio	RCA x 1
Local Output	RCA x 1
Record	
Record Stream	Dual Stream Recording
Resolution	8 MP, 5MP, 4 MP, 3 MP, 1080p, 960p, 720p
Mode	Manual, Timer, Motion, Sensor, Intelligence
Playback	-
Simultaneous Playback	16 Channel
Search	Thumbnail, Time, Event, Tag Search
Function	Play, Pause, FF, FB, Digital Zoom, etc. up to 32x
Alarm	,
Mode	Manual, Sensor, Motion, Exception, Intelligence
Input	16 Ch Local Alarm Input, Support IPC Alarm Input
Output	4 Ch
Triggering	Record, Snap, Preset, E-mail, etc
Network	Necestary straight research 2 main, etc.
Interface	RJ45 10/100/1000 Mbps x1
Protocol	TCP/lp, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Max 10 Users Online
Mobile Device	IVIDA TO OSCIS OTIMIC
OS	iOS, Android
	103, Al diold
Storage HDD	SATA x 8
טטוו	Running firmware version v1.2.x or newer will support Western Digital Purple 10TB Seagate Skyhawk 12TB
eSATA	e-SATA x 1 - max, single drive, 12TB WD and 14TB Seagat for Recording only
Backup	
Local Backup	USB, USB Mobile HDD
Network Backup	Yes
Port	
USB	USB 2.0 x 1 (Front Panel), USB 3.0 x 1 (Rear Panel)
Remote Controller	Yes
Other	
Power Supply	100-240 VAC
Consumption	< 15W (Without HDD)
Dimensions	16.92 x 17.71 x 3.54 Inches (430 x 450 x 90mm)
Work Environment	14°~122° F (-10° ~ 50°C)

Ordering Information PN1A-32X16F: 32 Ch, 16 PnP Ports, Facial Rec Also available with: 4, 8, 10, 12, 16, 32, 48, 64 TB