

EXTERNAL ANNUNCIATOR

BTTY-ANN-004

Product Features

- NEMA 4 Enclosure
- LED alarm indicators
- Works with FLEX BBU models
- Quick connection with BBUs
- IFC 2015, 2018, 2021 Edition
- NFPA 72 2013 Edition, NFPA 1221 2016 2019 Edition
- UL2524 2nd Edition Listing with SGS, Nationally Recognized Testing Laboratory (NRTL) approved by OSHA for UL2524.
- Buy American Compliant: Meets the definition of Domestic Construction Material under the Buy American Act



Specification

Specification	Value
Type	External Annunciator for FLEX BBU
Alarm Display	8 LED's
Alarms Displayed	AC Power Normal AC Fail - Batt Active Battery Capacity < 30% Battery Charger Fail Donor Antenna Disconnect Donor Antenna Malfunction RF Emitter Fail System Component Fail
Audible Alarm	Yes
Mute button for Audible Alarm	Yes
Maximum number of Annunciator	4
BBU interconnection	CAT 5/6
Conduit connector	Yes
Enclosure Rating	NEMA 4
Color	Red
Temperature Range	0 to 50 C
Dimensions	190 x 190 x 100 mm • 7.4 x 7.4 x 3.9 in
Weight	1.5 kg • 3.3 lbs

DOC BD428.01 • 10212021 • DMC
Fiplex is a registered trademark of Fiplex Communications, Inc.
Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

