











FUNCTIONS


- 5MP (2592 x 1944)
- Fixed 2.8mm Lens
- HD-TVI / CVI / AHD / CVBS (Analog)
- Easy-to-Use DIP Switch to Change Formats
- True Day / Night
- Smart IR Illumination Up to 66ft.
- Digital NR
- Defog
- DWDR
- IP67 Outdoor Rating
- DC 12V (4W Consumption)
- NDAA Compliant


5MP HD-TVI FIXED TURRET CAMERA

5MP HDI-TVI FIXED TURRET CAMERA WITH HD OVER COAX FEATURES

Our Second Generation HD-TVI Series continues providing the quality expected from the AVYCON brand. This 5MP camera includes an upgraded Smart IR LED array, new DIP switch design for easily changing video formats (HD-TVI, CVI, AHD and Analog), and a sleek new magnetic ring designed to hide all mounting screws from view and create a seamless body look. With the newest generation chipset and board design, we have also increased power efficiency with a possible 20% savings in consumption. Also standard with this series is Digital NR, AGC, WDR, BLC, and Defog capabilities along with IP67 outdoor rating.

DIMENSIONS





OPTIONAL ACCESSORIES



AVM-JB-BE-S1 JUNCTION BOX



AVM-CWM-FV-S1 COMPACT WALL MOUNT



AVM-HWM-E-S1 HEAVY-DUTY WALL MOUNT



AVM-HCM-F-S1 CEILING MOUNT



ΔVM-CRM-Δ1 CORNER MOUNT



ΔVM-PΩM-Δ1 POLE MOUNT

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.7" Progressive Scan CMOS
Resolution	5MP
Image Size	2592 x 1944
Video Output	1-channel BNC Video Output
Image System	PAL / NTSC
Electronic Shutter	1/15s to 1/50,000s
IR Distance	Up to 66ft.
Video Formats	HD-TVI / ADH / CVI / CVBS (Analog)
Frame Rate	5AHD/5TVI: 5MP @20fps (NTSC / PAL)
	AHD/CVI/TVI: 4MP @30fps (NTSC) / @25fps (PAL), 2MP @30fps (NTSC) / @25fps (PAL)
	0.05lux@F1.2(AGC ON),0Lux with IR ON
	Fixed 2.8mm Lens
Lens Mount	M12
S/N Ratio	
	OSD, Control over Coax (UTC)
IMAGE	
Day & Night	EXT / Auto / Color / BW (Black and White)
Digital WDR	
	Yes (3D DNR)
Auto Gain Control (AGC)	Yes
Auto White Balance (AWB)	Yes
Backlight Compensation (BLC)	Yes
Edge Brightness Compensation	Yes
	No
	No
Sharpness	Yes
Mirror Image	
Smart IR (Anti-SAT)	
Image Setting	
Defect Correction	Auto / Manual
GENERAL	
Angle Adjustment	
	DC 12V (±10%)
Power Consumption	
Ingress Protection	
	-22F - 131F (-30°~55° Celcius)
Dimensions	3.92" x 3.32" (100.5mm x 85.2mm)

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com