760252343 | PPL-DM-12U-12LC-0M4-BEU



Propel ULL Multimode OM4 MPO-12 Distribution Module, 6 duplex LC to 1X12f MPO/UPC non-pinned, Method B Enhanced

- Ultra-low loss (ULL) with Method B Enhanced polarity
- Can be installed and removed from front or rear of panel
- Serialized QR code provides easy access to factory optical test results
- This component requires 3 of the 12 lanes on the Propel Panel blade

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®

Product Type Fiber module

Product Brand Propel
Product Series PPL

General Specifications

Color, frontAquaColor, rearGray

Interface, front LC with Internal Shutters

Interface Feature, front Standard

Interface, rear MPO Unpinned with Internal Shutters

Interface Feature, rear Key up/up | UPC

Polarity Method B Enhanced (ULL)

Total Fibers, quantity 12

Total Ports, quantity, front 6

Total Ports, quantity, rear 1

Dimensions

 Height
 11 mm | 0.433 in

 Width
 98 mm | 3.858 in

 Depth
 170 mm | 6.693 in

Optical Specifications

Fiber Mode Multimode

Page 1 of 2

760252343 | PPL-DM-12U-12LC-OM4-BEU

Fiber Type OM4, LazrSPEED® 550

Insertion Loss, maximum 0.35 dB

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL | UL 62368

Packaging and Weights

Packaging quantity 1

