



Propel sliding tray fiber panel, accepts Propel ULL modules or adapter packs, providing up to 72 duplex LC ports, 72 MPO ports or 288 SN ports

- Any size Propel component can be used in each panel or blade
- Components can be installed and removed from front or rear of panel
- Supports 8f, 12f, 16f and 24f applications while maintaining full panel density
- Cable mounting system allows for multiple trunk cables to be securely attached in the rear of panel

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber patch panel
Product Brand	Propel
Product Series	PPL

General Specifications

Access	Front Rear
Color	Gray
Rack Type	EIA 19 in
Rack Units	1
Shelf Movement	Sliding

Dimensions

Height	44 mm 1.732 in
Width	483 mm 19.016 in
Depth	470 mm 18.504 in

760252002 | PPL-1U

Port Configuration

Product Number	8-fiber components	12-fiber components	16-fiber components	24-fiber components
PPL-1U	up to 6 per blade up to 18 per panel	up to 4 per blade up to 12 per panel	up to 3 per blade up to 9 per panel	up to 2 per blade up to 6 per panel
PPL-2U	up to 6 per blade up to 36 per panel	up to 4 per blade up to 24 per panel	up to 3 per blade up to 18 per panel	up to 2 per blade up to 12 per panel
PPL-4U	up to 6 per blade up to 72 per panel	up to 4 per blade up to 48 per panel	up to 3 per blade up to 36 per panel	up to 2 per blade up to 24 per panel
Each Blade has 12 Lanes				
	Requires 2 lanes	Requires 3 lanes	Requires 4 lanes	Requires 6 lanes

Material Specifications

Material Type Aluminum | Steel

Packaging and Weights

Packaging quantity 1

Weight, net 5.375 kg | 11.85 lb