

760252352 | PPL-DM-16AU-16LC-SM-BEU



Propel ULL Singlemode MPO-16 Distribution Module, 8 duplex LC/UPC to 1X16f MPO/APC non-pinned, Method B Enhanced

- Ultra-low loss (ULL) with Method B Enhanced polarity
- Can be installed and removed from front or rear of panel
- Serialized QR code provides easy access to factory optical test results
- This component requires 4 of the 12 lanes on the Propel Panel blade

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber module
Product Brand	Propel
Product Series	PPL

General Specifications

Color, front	Blue
Color, rear	Gray
Interface, front	LC with Internal Shutters
Interface Feature, front	UPC
Interface, rear	MPO16 Unpinned with Dust Caps
Interface Feature, rear	APC Key up/up
Polarity	Method B Enhanced (ULL)
Total Fibers, quantity	16
Total Ports, quantity, front	8
Total Ports, quantity, rear	1

Dimensions

Height	11 mm 0.433 in
Width	131 mm 5.157 in
Depth	170 mm 6.693 in

Optical Specifications

Fiber Mode	Singlemode
-------------------	------------

760252352 | PPL-DM-16AU-16LC-SM-BEU

Fiber Type	OS2
Insertion Loss, maximum	0.6 dB

Environmental Specifications

Qualification Standards	IEC 61753-1 TIA-568.3-D
Safety Standard	CE CSA UL UL 62368

Packaging and Weights

Packaging quantity	1
---------------------------	---