



Propel sliding tray fiber panel, accepts Propel ULL modules or adapter packs, providing up to 288 duplex LC ports, 288 MPO ports or 576 SN ports

- Any size Propel component can be used in each panel or blade
- Components can be installed and removed from front or rear of panel
- Supports 8f, 12f, 16f and 24f applications while maintaining full panel density
- Cable mounting system allows for multiple trunk cables to be securely attached in the rear of panel

Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Portfolio	CommScope®
Product Type	Fiber patch panel
Product Brand	Propel
Product Series	PPL

General Specifications

Access	Front   Rear
Color	Gray
Rack Type	EIA 19 in
Rack Units	4
Shelf Movement	Sliding

Dimensions

Height	178 mm   7.008 in
Width	483 mm   19.016 in
Depth	470 mm   18.504 in

# 760252004 | PPL-4U

## Port Configuration

Product Number	8-fiber components	12-fiber components	16-fiber components	24-fiber components
PPL-1U	up to 6 per blade up to 18 per panel	up to 4 per blade up to 12 per panel	up to 3 per blade up to 9 per panel	up to 2 per blade up to 6 per panel
PPL-2U	up to 6 per blade up to 36 per panel	up to 4 per blade up to 24 per panel	up to 3 per blade up to 18 per panel	up to 2 per blade up to 12 per panel
PPL-4U	up to 6 per blade up to 72 per panel	up to 4 per blade up to 48 per panel	up to 3 per blade up to 36 per panel	up to 2 per blade up to 24 per panel
Each Blade has 12 Lanes				
	Requires 2 lanes	Requires 3 lanes	Requires 4 lanes	Requires 6 lanes

## Material Specifications

**Material Type** Steel

## Packaging and Weights

**Packaging quantity** 1

**Weight, net** 14.742 kg | 32.5 lb