

PRODUCT-DETAILS

JSTD1-A

JSTD1-A Safeball



General Information

Extended Product Type	JSTD1-A
Product ID	2TLA020007R3000
EAN	7350024460193
Catalog Description	JSTD1-A Safeball
Long Description	JSTD1-A Safeball, 1NO + 1NC, 2 m cable (4 leads). Ergonomic design with several grip possibilities and low activation force (approx. 2N) and flexible mounting options. Provides highest level of safety for use in two hand control applications when using two Safeballs in conjunction with appropriate safety relay or Pluto Safety PLC. Maximum load of 30VDC, 2A resistive, IP67 protection degree, plastic body.

Additional Information

Product Name	Safeball
Function	One- and two-hand device

Safety Information

Certification Agency	Inspecta
Performance Level (PL)	Up to e

Technical

Contacts Configuration	1 NO, 1 NC
Connection	Cable

Configuration

Cable Length	2 m
--------------	-----

Environmental

Degree of Protection	IP67
Ambient Air Temperature	Operation -25 ... 50 °C
Material	Housing: Polypropylene Cable: PVC

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
Data Sheet, Technical Information (Part 2)	2TLC010064D0201
Instructions and Manuals	2TLC172182M0201

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2TLC172023D0201
Instructions and Manuals	2TLC172182M0201
SEMKO Certificate	2TLC172034D0201

Dimensions

Product Net Width	72 mm
Product Net Depth / Length	72 mm
Product Net Height	71 mm
Product Net Weight	0.225 kg

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8536201090

Classifications

Object Classification Code	B
ETIM 7	EC002611 - Control switch
ETIM 8	EC002611 - Control switch
eClass	V11.0 : 27371414
UNSPSC	32151802

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSTD1

