

SPECIFICATIONS

[General Specifications]

Model		SKH-12EA	SKH-24EA	SKH-100EA	SKH-200EA
Rated Voltage		12V DC	24V DC	100V AC (50/60Hz)	200V AC (50/60Hz)
Operating Voltage Range		9V ~ 16V DC	20V ~ 30V DC	90V ~ 110V AC	180V ~ 220V AC
Rated Current Consumption		0.8 A	0.5 A	65 mA	30 mA
Rated Power Consumption		9.6 W	12.0 W	6.2 W	6.5 W
Operating Ambient Temperature		- 30 °C to + 80 °C		- 30 °C to + 60 °C	
Operating Ambient Humidity		Less than 90 % (No condensation)			
Storage Ambient Temperature		- 30 °C to + 80 °C		- 30 °C to + 60 °C	
Storage Ambient Humidity		Less than 90 % (No condensation)			
Mounting Location		Indoors and Outdoors			
Mounting Direction		【Indoors】 Upright ,Inverted and Sideways / 【Outdoors】 Upright			
Protection Rating		IP23 (IEC 60529)			
	Environmental Condition	Upright only			
Vibration Resistance		70 m/s ² (JIS D 1601-1995)		45 m/s ² (JIS D 1601-1995)	
Insulation Resistance				More than 1MΩ at 500VDC between the terminals and the chassis	
Withstand Voltage				The following voltage applied for 1min between terminals and chassis without breaking insulation	
				1000V AC	1500V AC
Flashing Rate		170 ± 25 Flashes Per Minute			
Bulb		12V 10W	24V 10W	12V 5W	
		Base : BA15S / Bulb : G18			
Luminous Intensity (No Globe)		8,000 cd	5,200 cd	3,340 cd	
Mass (Tolerance ±10%)		0.4 kg		0.6 kg	
Outer Dimensions		Refer to the Outer Dimension Drawing			
Conformity Standards		EMC Directive (EN 61000-6-4, EN 61000-6-2) RoHS Directive (EN IEC 63000)			
Remarks		Conforms to the CE requirements			

【Model Number Configuration】

SKH — EA —

- Globe Color / Case Color
 - R : Red / Red
 - Y : Amber / Amber
 - G : Green / Light Gray
 - B : Blue / Light Gray

- Rated Voltage
 - 12 : 12V DC
 - 24 : 24V DC
 - 100 : 100V AC
 - 200 : 200V AC

