

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: Anixter

TOL Part Number: XHHW/SIS-F-14-1005
Spec Revision Level: A9

Description: 14 AWG (2.08mm²) XHHW-2 & SIS (VW-1) DUAL RATED, XLPE
INSULATED 90°C 600V, 41 STRANDS TINNED

Conductor (Stranding): 41 X 30 AWG Tinned Copper, UL
Conductor OD (Nom) 0.069 inches
Max. Lay Length: 1.5 inch Lay
Min Avg Wall Thickness: 0.030 inches
Min. O.D: 0.129 inches
Nom. O.D: 0.132 inches
Max Runout: 0.008 inches
Strip Force: 1" Strippable
Circular Mils (CMA): 3898

Surface Print: 14 AWG (2.08mm²) (UL) XHHW-2 OR SIS VW-1 600V E7088 CSA c(UL) R90
600V FT1 FT2 LL25850

This product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
Packard: N/A	Other: UL STD 44 / CSA 22.2#127-18	

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.
Verified By: Kevin Trembath (Product Engineering Manager)
Date: 3-22-2023