

**Evolv® 2-Port Terminals with Pushlok™  
Technology, Stubbed Long Span Evolv® 2-Port  
Terminals with Pushlok™ Technology, Stubbed  
Long Span, 250 ft**

CORNING

**Part Number:  
DMA2F1LSD1NC250F0P**

# Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span, 250 ft

CORNING

## Specifications

General Specifications	
Product Type	Evolv® Terminal™
Environment	Outdoor
Cable Type	Long Span All-Dielectric
Fiber Category	ITU-TG.652.D (OS2)
Packaging	Individual Pack
Preconnectorized "Stubbed" Hardware	No
Mounting Type	Strand mount, Pole-mount, Pedestal mount, Handhole Mount
Splice option	No
Application	FTTx
Technology	Pushlok™

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Fiber Count	2
Input Fiber Count	2
Fibers per Port	1
Number of single-fiber ports, SC APC connector	2
Housing Material	Plastic
Adapter Type Master Level	Plastic
Adapter Color Front	Black
Adapter Type Front	Pushlok™
Polish	Angled Polish
Housing Type	Outdoor

Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span, 250 ft



Design	
Input Cable Type	Long Span All-Dielectric
Sealing Type	Welded
Housing Color	Black
Color	Black
Product Family	Evolv® Terminal™
Number of Ports	2

Cable Design	
Fiber Count	2

Design - Adapter	
Housing Color	Black
Housing Material	Plastic
Adapter Style	SC APC
Adapter Type	Pushlok™

Mechanical Specifications	
Cable Length	76.2 m (249.94 ft)
Cold Mate/Demate	-40 °C (-40 °F)

Connector Specs	
Housing Color	Black
Housing Material	Plastic

Specifications - Connector A	
Connector Type	Pushlok™

# Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span Evolv® 2-Port Terminals with Pushlok™ Technology, Stubbed Long Span, 250 ft

CORNING

## Specifications - Connector A

Polish	Angled Polish
Endface Type	SC APC
Insertion Loss, Max.	0.5 dB
Reflectance	> 65 dB

## Dimensions

Height	2997 mm (117.99 in)
Width	83.56 mm (3.29 in)
Depth	15392 mm (605.98 in)

## Ordering Information

Product Number	DMA2F1LSD1NC250F0P
Packaging Method	Box
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2024 Corning Optical Communications. All rights reserved.