

4K UHD

R4N(UHD) Series 4K VIDEO WALL ULTRA NARROW BEZEL

LED

R4N49NNU




The R4N (UHD) Series of LCD Displays is the perfect solution for ultra-high definition video walls. Equipped with a standalone 3840 x 2160 resolution panel and the ability to take a single video source and displaying across the entire Video Wall; it is an excellent choice for command & control centers, corporate, AV and digital signage applications.



Video Walls for Security Center, Control Rooms, Commercial AV, Professional AV


The R4N monitor series can be used for applications in shopping malls, airports, stadiums, lobby signage and boardrooms just to name a few. Whether a small lobby display or an extra large video wall, the R4N series makes a statement. Public display signage with dynamic content receives far more eye contact than with static content and creates cost effective opportunities to improve brand recognition, customer service, safety, training and communications.

Unlike plasma technology, LCD video walls require less power and our built in auto pixel shift feature prevents against image burn in of static content. Individually mounted consumer grade monitors leave gaps between the monitors but with our super & ultra narrow bezels, there are virtually no gaps between monitors in a tiled video wall.



- » Security / Control Rooms
- » Retail
- » Universities & colleges
- » Corporations
- » Transportation
- » Health Care & Medical
- » Government
- » Financial Institutions
- » Hospitality
- » Casino

VIDEO WALL REFERENCE




SPECIFICATIONS

R4N49NNU	
Bezel Width	
Top / Bottom / Left / Right	9.4mm / 9.4mm / 10.7mm / 10.7mm
Display	
Screen Size	48.5 Inch
Max. Resolution	3840 x 2160 @ 60Hz
Pixel Pitch	0.27963 x 0.27963mm
Brightness	500cd/m ²
Contrast Ratio	1100 : 1
Aspect Ratio	16 : 9
Viewing Angle	178° / 178°
Display Color	1.07 Billion (10bits)
Response Time	< 8ms (Gray to Gray)
Video System	NTSC / PAL
Interface	
Display Port In/ Out	1 / 1
HDMI Input	3
DVI In	1
VGA In	1
RS232 In / Out	1 / 1
Audio Out (3.5 Ø stereo)	1
Transmitter	
IR Remote Control	Yes
Features	
Multi Display Function	PBP / PIP / TRI / QUAD
Temperature Sensor	Yes (Option)
De-Interlace	Yes
Noise Reduction	Yes
Auto Fan Control System	Yes (Option)
Auto Pixel Shift	Yes
Auto Source Switching	Yes
Edge Setting (Horizontal / Vertical)	Yes
Advance Auto Power Recovery	Yes
Multi Language	English
RS-232C Control	Monitor OSD control using PC
Cabinet	
Color	Black
Material	Electro-Galvanized Steel
Outline Dimension	
Dimension (W x H x D)	(43.19" x 24.80" x 2.6" (1097.2 x 630 x 66.1mm)
Net. Weight	26kg (57.32 lbs)
Warranty	
Part / Labor	3year / 3year
Circumastance	
Operating Temperature	0° ~ 40° C / 32° ~ 104° F
Power	
Electrical Ratings	AC 120 ~ 240V (50/60Hz)
Power Consumption	< 100W
Mount	
VESA™ Mount Size	600 x 400mm
Video Wall	WFS, WES, WSD, WSR, CCM
Stand Alone	WB-3770, WB-4370

* Specifications and design are subject to change without notice.

MOUNTS




HARDWARE


Hardware features:

- » Spread 1 image across multiple monitors using 1 video source
- » Video Wall Processor built in
- » Remote Display Management (IR Remote or Mobile WIFI)
- » Display Port 1 In / 1 Out
- » HDMI 3 In / VGA In / DVI In
- » RS-232C In / Out for pc / server control
- » Control panel Lock (panel or IR)
- » All metal chassis
- » Auto power recovery
- » Auto pixel shift
- » PIP / PBP / TRI / QUAD Displays
- » VESA standard hole patterns

INTERFACE



DIMENSION



*Design and specifications are subject to change without notice