

L3 Series AI 4MP IP Outdoor Turret Camera



2.8mm, True WDR, Full Color, IP66, PoE



L3IP4TFCS



L3IP4TFCS



FEATURES:

- ◆ NDAA Compliant
- ◆ Supports AI Face, Body & Vehicle Recognition*
- ◆ True 120dB Wide Dynamic Range
- ◆ 4MP Resolution (2560×1440)
- ◆ Fixed 2.8mm Lens
- ◆ Full Color, 3 White Light LED - 100' Range
- ◆ 7 Intelligent Analytics
- ◆ 256GB SD Card Capability
- ◆ H.265 Recording Compression
- ◆ Built in Mic & Alarm
- ◆ PoE - Power over Ethernet
- ◆ Onvif Profile S/G/T Compliant
- ◆ IP66 Weatherproof

INCLUDED ACCESSORIES:

- 1x Quick start guide
- 3x Mounting inserts & screws
- 1x Mounting template
- 1x Network cable cover w/gasket
- 1x 4 Pin Terminal block

	FEATURES	L3IP4TFCS
Camera	Image Sensor	1/1.8" Progressive Scan CMOS
	Minimum Illumination	Color: 0.0005 Lux @ (F1.0, AGC ON), 0.0 Lux with white light On
	S/N Ratio	55dB
	IR LED Count / Range	3 White Light LEDs / 100' Range
	Shutter Time	1/5s - 1/20,000s
	Lens (IR Corrective)	Fixed 2.8mm - Angle of View 105°
	Camera Bracket Adjustment	Pan: 0° ~ 355°, Tilt: 0° ~ 80°, Rotation: 0° ~ 360°
	Day & Night	Yes - True Day/Night with IR Filter - Auto Switch
	DNR (Digital Noise Reduction)	2DNR & 3DNR, Auto / Manual (0-100 Adjustable)
	True Wide Dynamic Range (120dB)	On / Off (0-100 Adjustable)
	BLC (Backlight Compensation)	On / Off (0-100 Adjustable)
	AI Recognition	* Face, Body & Vehicle Recognition for use with Liberty L3 Series NVRs
	Intelligent Analytic Features	Perimeter, Single Virtual Fence, Double Virtual Fence, Multi Loitering, Wrong Way, People Counting, Smart Motion
	Region of Interest	Yes
Resolution/Bitrate	Video Compression	H.265, H.264, MJPEG (for all stream types)
	Audio Compression	G.711, RAW_PCM
	General Functions	Supports Mirror, Aisle Mode, Smart IR, Password Protection, Privacy Mask, Motion Detection
	Max. Resolution	2560x1440 (4MP)
	Mainstream Resolution / FPS	2560x1440, 2304x1296, 1920x1080, 1280x720 @25/30FPS
	Substream Resolution / FPS	D1, VGA, 640x360, CIF @25/30fps
Network	Third Stream Resolution / FPS	VGA, CIF, QVGA @25/30FPS
	Audio Bitrate	8kbps, 16kbps, 64kbps
	Video Bitrate	Main: 200kbps~12Mbps
		Sub: 100kbps~6Mbps
Interface	Protocols	IPV4/IPV6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTSP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
		Up to 10 Users
	Client Software	Liberty CMS, Liberty-View Mobile App, Liberty Tools
	Web Browser	<IE11, Chrome, Safari, Edge
General	Communication Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
	Audio	1Ch Input/Output (3.5mm) Built in Mic
	Alarm	1Ch Input/Output (Screw Terminal Connector)
	Reset Button	Yes
General	Onboard Storage	Yes Built in Micro SD/SDHC/SDXC slot, up to 256GB
	Operating Conditions	-40°C ~ 55°C (-40°F ~ 131°F), Less than 90% RH
	Power Supply	12VDC / POE (IEEE 802.3af)
	Power Consumption & Current	3.5W (LED OFF), 6W Max (LED ON)
	Weatherproof/ Impact Ratings	IP66
	Housing Material / Color	Aluminum / White
	Overall Camera Dimensions	Ø4.6" x 3.7" (Ø118x94mm)
General	Net Weight	1.2lb / .55kg
	Certifications	CE / FCC / NDAA

L3 Series AI 4MP IP Outdoor Turret Camera

2.8mm, True WDR, Full Color, IP66, PoE



L3IP4TFCS

Optional Mounting Accessories for L3IP4TFCS:


L3JB3 Junction box

Features:

- ◆ Manages & Protects Cables
- ◆ 3/4" Conduit Access
- ◆ For Indoor & Outdoor Use



L3JB3



L3JB3 Lineart


L3HWM1 Wall mount

Features:

- * Requires L3PC3 Pendant Cap
- ◆ Manages & Protects Cables
- ◆ Hinged Wall Arm for Easy Installation
- ◆ Side, Back & Bottom 3/4" Conduit Access
- ◆ For Indoor & Outdoor Use



L3HWM1



L3HWM1 Lineart


L3PC3 Pendant cap

Features:

- ◆ Pendant Mount for Dome Camera
- ◆ Aluminum Alloy
- ◆ For Indoor & Outdoor Use



L3PC3



L3PC3 Lineart


L3CPM1 Pendant mount

Features:

- * Requires L3PC3 Pendant Cap
- ◆ 18" Drop Down Length
- ◆ For Use With or Without Drop Down Pipes
- ◆ Includes (2) 9" Drop Down Pipes
- ◆ Manages & Protects Cables
- ◆ For Indoor & Outdoor Use



L3CPM1



L3CPM1 Lineart


L3POLEMT2 Pole mount

Features:

- ◆ Metal Straps Included
- ◆ For 5-6" Pole Diameters
- ◆ For Indoor & Outdoor Use



L3POLEMT2



L3POLEMT2 Lineart