

5MP Multi Format Outdoor Bullet Camera

2.8mm, True WDR, 80' IR, IP67

5MP

NDAA

4-in-1



2.8mm

IR LED

LA5BIR80



LA5BIR80



FEATURES:

- ◆ NDAA Compliant
- ◆ Supports TVI, CVI, AHD & 960H Formats
- ◆ 5MP Resolution (2560×1944) @20FPS
- ◆ True 120dB Wide Dynamic Range
- ◆ True Day/Night IR Cut Filter
- ◆ Fixed 2.8mm IR Lens
- ◆ Up to 80' IR Range
- ◆ UTC & Cable OSD Control
- ◆ 12 Volt DC Power
- ◆ IP67 Weatherproof

INCLUDED ACCESSORIES:

- 1x Quick start guide
- 1x Hex wrench
- 4x Mounting inserts & screws
- 1x Mounting template

	FEATURES	LA5BIR80
Camera	Image Sensor	1/2.8" CMOS
	Scanning System	Progressive Scan
	Resolution	5MP (2560×1944)
	Signal System	NTSC / PAL
	Shutter Speed	Auto, Manual 1/25 ~ 1/10,000
	Minimum Illumination	Color: 0.01 Lux @ (F1.2, AGC ON); B/W: 0 Lux @ (IR LED ON)
	S/N Ratio	More than 50dB
	Sync System	Internal
	Camera Bracket Adjustment	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°
	Camera Bracket Adjustment	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°
Lens	Lens Type / Viewing Angle	2.8mm IR Lens / H: 90.4°, V: 65.8°
	True Day/Night	Yes - Removeable IR Cut Filter
	IR LED Count / Range / nM	24 IR LED's / 80' Range / 850nm
Video & OSD	Video Output	Single BNC Output - Supports TVI, CVI, AHD & 960H Formats (Selectable via OSD Cable)
	Frame Rate	AHD/TVI: 5MP @ 20/12.5fps, 4MP @ 25/30/15fps, CVI: 4MP @ 25/30fps, CVBS: PAL/NTSC
	True WDR (Wide Dynamic Range)	Yes- 120dB
	OSD (On Screen Display)	Dual OSD Access: Cable OSD Controlled / UTC Controlled (coaxial control)
	Day & Night	Yes - True Day/Night with IR Filter - Auto Switch
	DNR (Digital Noise Reduction)	2DNR & 3DNR, Auto / Manual (0-100 Adjustable)
	Automatic Gain Control	Auto, Manual 0 ~16 Adjustable
	Gamma Characteristics	y = 0.45 typ
	White Balance	ATW, MWB - R & B Gain 0~32 Adjustable
	Back Light Compensation	Globe / BLC / 1~8 Adjustable
	Day/Night	EXT / Auto / Color / B/W
	Languages	English, French, Spanish, Italian (see OSD Menu for more)
	Brightness	0 ~30 Adjustable
	Brightness	0 ~30 Adjustable
General	Power Input	12 Volt DC Only ±10%
	Power Consumption & Current	Max. 4W (12V DC, IR ON)
	Overall Camera Dimensions	194.4× 64 × 64mm (7.63" × 2.52" × 2.52")
	Housing / Color	Aluminum / White
	Net Weight	0.49 kg (1.08 lb)
	Operating Temperature	-25 °C ~ 55 °C (-14°F ~ 131 °F)
	Weatherproof Rating	IP67

5MP Multi Format Outdoor Bullet Camera

2.8mm, True WDR, 80' IR, IP67

5MP

NDAA

4-in-1

2.8mm

IR LED

LA5BIR80

Optional Mounting Accessories for LA5BIR80:




L3JB1 Junction box

Features:

- ◆ Manages & Protects Cables
- ◆ 3/4" Conduit Access
- ◆ For Indoor & Outdoor Use



L3JB1



L3JB1 Lineart




L3POLEMT2 Pole mount

Features:

- ◆ Metal Straps Included
- ◆ For 5-6" Pole Diameters
- ◆ For Indoor & Outdoor Use



L3POLEMT2



L3POLEMT2 Lineart