



LVBPAIR

Video Balun with Bare Lead
to 4" BNC Pigtail



LVBPAIR

SPECIFICATION	LVBPAIR
Connections	Screw Terminal to BNC Male w/4" Pigtail
Video Signal	1Vp-p, 75 Ohms
Transmission Distance	350M (960H/720P), 250M (1080P), 200M (4MP-5MP)
ESD Protection	30KV (Air), 15KV (Contact); IEC 61000-4-2 Compliant
Cable Type	For Use with CAT5e/CAT6 UTP (Unshielded Twisted Pair)
EFT Protection	40A (5/50ns); IEC 61000-4-4 Compliant
Lightning Protection	2A (8/20µs); IEC 61000-4-5 Compliant
Surge Protection Attack Time	< 1nS
Dimensions	7.2" x 0.6" x 0.5" / 113mm x 16mm x 13mm
Net Weight	.1lb / .04kg
Country of Origin	Made in China



LVPBPAIR

Video/Power Balun with RJ45 to 4"
BNC Pigtail & Power Leads



LVPBPAIR

FEATURES:

- ◆ BNC Male to RJ-45
- ◆ 6' BNC Pigtail
- ◆ DC Male & DC Female Power
- ◆ Passive, no Power Required
- ◆ 350M (960H/720P), 250M (1080P)
- ◆ 200M (4MP-5MP)
- ◆ Passive, No Power Required
- ◆ Built-in ESD, EFT & Transient Protection



Interlocking Design

SPECIFICATION	LVPBPAIR		
Connections	Video: RJ-45 to BNC Male w/ 6" Pigtail Power: 12VDC Male to 12VDC Female		
Video Signal	1Vp-p, 75 Ohms		
Transmission Distance	350M (960H/720P), 250M (1080P), 200M (4MP-5MP)		
ESD Protection	30KV (Air), 15KV (Contact); IEC 61000-4-2 Compliant		
Cable Type	For Use with CAT5e/CAT6 UTP Cable		
Supports 12VDC & 24VAC Power	Supports 12VDC & 24VAC Power		
EFT Protection	40A (5/50ns); IEC 61000-4-4 Compliant		
Lightning Protection	2A (8/20μs); IEC 61000-4-5 Compliant		
Surge Protection Attack Time	< 1nS		
Dimensions	81mm x 20mm x 30mm (body) w/ 6" BNC & Power Pigtails		
Net Weight	.2lb / .09kg		
Country of Origin	Made in China		
LVPBPAIR Distance/Voltage Requirements			
Distance	Desired Voltage / Amperage		
	12VDC / 0.5A	12VDC / 1Amp	12VDC / 1.5A
	Starting Voltage Required		
50M	13.5V	15.5V	17.0V
100M	15.5V	18.5V	22.0V
150M	17.0V	22.0V	27.0V
200M	18.5V	25.5V	32.0V
300M	22.0V	30.0V	42.0V