

Part Number: DSD Series Single Link DVI-D



Single Link DVI-D Cable Assembly

Product Description

Single Link DVI-D Cable Assembly, 1920 x 1200 (WUXGA) @ 60Hz, 3.96Gbits/sec.

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	Digital Signage, Computer Monitors, Projectors, Gaming Consoles, DVD Players

Physical Characteristics (Overall)

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]
Tape	Aluminum/Mylar	Beldfoil AL/Mylar	100 %
Braid	TC - Tinned Copper		80 %

Outer Jacket Material

Material	Nominal Diameter
PVC	.276 in

Electrical Characteristics

Voltage

Voltage Rating [V]
30V

Electrical Characteristics Notes:	Nominal Attenuation @ 825 MHz 8dB
Performance Footnote1:	Intrapair Delay Skew 150 ps
Performance Footnote2:	Interpair Delay Skew 2420 ps

Temperature Range

Operating Temp Range:	0°C To +80°C
-----------------------	--------------

Mechanical Characteristics

Max Recommended Pulling Tension:	39 lbs
----------------------------------	--------

Termination Interface

Connection
DVI 18+1 Male

Standards

UL Rating:	AWM 20276
------------	-----------

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1581 Vertical Tray & VW-1
------------------	-----------------------------

Part Number

Variants

Item #	Color	Length
DSD003FB	Black	3 ft
DSD006FB	Black	6 ft
DSD010FB	Black	10 ft
DSD013FB	Black	13 ft
DSD015FB	Black	15 ft

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.